

CUBIX II - Acoustic

Outer Acrylic Interior Pendant








9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@lighting.com www.lighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.
Acoustic Panel: 1/2" center acoustic panel reduces noise level in environment.
Lower Output: Lamping code ending with LO features lower lumen output.
LED Dimming: Standard 1% 0-10V dimming.
Cable Hanger: Standard 150" cable and white cord for on-site adjustability. Canopy painted textured white.
Canopy: Max remote driver installation distance: White LED 25ft from fixture body and RGB 45ft from fixture body. See Cubix Hanger Guide for more information.
Finish: Highly durable oven cured no VOC premium powder coat.
RGB: DMX controller supplied by others.
Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2832-	J-	BLK-	ABLK-	1-	A	
MODEL NO.	LAMPING		FINISH	ACOUSTIC	HANGER	OPTIONS
GL-2830 10lbs W in 24"x24" 4.5kg B in 3" H in 11"-145"	A. 24LED30 B. 24LED35 C. 24LED40 D. RGB	AL. 24LED30LO BL. 24LED35LO CL. 24LED40LO	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue	Standard: Acoustic ABLK-Black ABL-Blue AGR-Gray ALG-Light Gray ARD-Red	1. Cable - Standard  Drivers mounted remotely. See Cubix Hanger Guide for more information.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-2831 15lbs W in 36"x36" 6.8kg B in 3" H in 18.75"-145"	E. 36LED30 F. 36LED35 G. 36LED40 H. RGB	EL. 36LED30LO FL. 36LED35LO GL. 36LED40LO			2. Oversized  Drivers mounted inside oversized canopy. See Cubix Hanger Guide for more information.	
GL-2832 15lbs W in 48"x48" 6.8kg B in 3" H in 18.75"-145"	I. 48LED30 J. 48LED35 K. 48LED40 L. RGB	IL. 48LED30LO JL. 48LED35LO KL. 48LED40LO			3. Vertical Remote Canopy  Drivers mounted remotely. See Cubix Hanger Guide for more information.	
GL-2833 19lbs W in 60"x60" 10kg B in 3" H in 25.5"-142"	M. 60LED30 N. 60LED35 O. 60LED40 P. RGB	ML. 60LED30LO NL. 60LED35LO OL. 60LED40LO	Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze		4. Vertical Integral Canopy  Drivers mounted inside 12.5" oversized canopy. See Cubix Hanger Guide for more information.	
GL-2834 22lbs W in 72"x72" 10kg B in 3" H in 25.5"-142"	Q. 72LED30 R. 72LED35 S. 72LED40 T. RGB	QL. 72LED30LO RL. 72LED35LO SL. 72LED40LO	Premium: SA-Satin Aluminum		Hanger options 1&3 supplied with remote driver box.	

All Dimensions are nominal.

Light Source Definition

High Lumen Output						Low Lumen Output					
Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin	Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
24LED30/35/40	78	+85	50000	6803	3000/3500/4000	24LED30/35/40LO	43	+85	50000	3605*	3000/3500/4000
36LED30/35/40	112	+85	50000	10203*	3000/3500/4000	36LED30/35/40LO	56	+85	50000	5102*	3000/3500/4000
48LED30/35/40	157	+85	50000	14682	3000/3500/4000	48LED30/35/40LO	85	+85	50000	7210*	3000/3500/4000
60LED30/35/40	193	+85	50000	18006	3000/3500/4000	60LED30/35/40LO	112	+85	50000	9523*	3000/3500/4000
72LED30/35/40	216	+85	50000	18503	3000/3500/4000	72LED30/35/40LO	134	+85	50000	10203*	3000/3500/4000
RGB	Contact Factory for Details										

Universal Voltage unless otherwise specified.

*Pending IES Testing