

CUMBERLAND

Indoor Surface Mount



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable. Universal voltage.


LED Dimming: Standard 1% 0-10V dimming with LED lamping option.


Body: GL-3040-3043 ring spun in 18ga steel or .050 aluminum.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



| SAMPLE CATALOG NUMBER: GL-3042- | | L45- | S- | NSN- | A |
|--|---|---|--|---|---|
| MODEL NO. | LAMPING | ACRYLIC | FINISH | OPTION(S) | |
| GL-3040 14lbs B in 18" mm 460 6 kg W in 24" mm 610 D in 8" mm 200 | IN3. 3MED* L30. 3LED30 F4. 4CF L35. 3LED35 L34. 3LED40 | Standard: S. Satin White Optional: W. White Opal F. Faux Alabaster M. Earth Marble | Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBN- Terra Brown TBZ- Textured Bronze Premium: SA- Satin Aluminum SB- Satin Brass PB- Polished Brass ORB- Oil Rubbed Bronze PC- Polished Copper SA- Satin Aluminum SC- Satin Chrome SN- Satin Nickel | A. No Options F. Add Finial  B. Damp Location Available in powder coat or Satin Aluminum finish. DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Ballast Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°- 131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. Multi-circuiting available upon request. | |
| GL-3041 21lbs B in 24" mm 610 10 kg W in 30" mm 765 D in 9" mm 230 | IN3. 3MED* L40. 4LED30 F4. 4CF L45. 4LED35 L44. 4LED40 | Acrylic is UL-94 HB Flame Class rated. | | | |
| GL-3042 29lbs B in 30" mm 760 13kg W in 36" mm 915 D in 10" mm 255 | IN6. 6MED* L40. 4LED30 F4. 4CF L45. 4LED35 L44. 4LED40 L60. 6LED30 L65. 6LED35 L64. 6LED40 | | | | |
| GL-3043 37lbs B in 38" mm 965 17kg W in 44" mm 1120 D in 11 1/2" mm 290 38" available in Satin Aluminum and powder coat finish only | IN6. 6MED* L60. 6LED30 F6. 6CF L65. 6LED35 L64. 6LED40 L80. 8LED30 L85. 8LED35 L84. 8LED40 | | | | |
| *120 Volt Only | | | | | |

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

| Code | Lamp | Fluorescent | Lamp Base | Lamp Lumens ¹ | Code | Total Wattage | Kelvin | Delivered Lumens |
|---------|------|----------------|--------------|--------------------------|------|---------------|--------|------------------|
| F4,F6 | CF | CF 26W/32W/42W | GX24q-3 4PIN | 1530/2040/2690 | L30 | 42 | 3000 | 4211 |
| IN3,IN6 | Med | A-19 | Medium | | L35 | 42 | 3500 | 4211 |
| | | | | | L34 | 42 | 4000 | 4211 |
| | | | | | L40 | 58 | 3000 | 5074 |
| | | | | | L45 | 58 | 3500 | 5074 |
| | | | | | L44 | 58 | 4000 | 5074 |
| | | | | | L60 | 87 | 3000 | 8063 |
| | | | | | L65 | 87 | 3500 | 8063 |
| | | | | | L64 | 87 | 4000 | 8063 |
| | | | | | L80 | 117 | 3000 | 12035 |
| | | | | | L85 | 117 | 3500 | 12035 |
| | | | | | L84 | 117 | 4000 | 12035 |

Universal Voltage unless otherwise specified.

¹Per MAXLITE & GE lamp products catalog

Contact factory for availability of other lamp configurations including induction and metal halide.