

DAVIT

Indoor ADA Sconce



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com



GENERAL SPECIFICATION

Lamping: Standard lamping packages offer long lamp life, high power factor energy efficient electronic ballast.

Acrylic: UL-94 HB Flame Class rated.

Standard Finishes: Highly durable oven cured no VOC premium powder coat.

Custom: Contact factory for custom lamping, acrylic, or sizing.



SAMPLE CATALOG NUMBER: GL-4535-				
MODEL NO.	E5-	W-	NSN-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
GL-4535 W in 10 3/4" mm 275 H in 11 1/2" mm 290 D in 3 3/4" mm 95	E0. 1LED30 E5. 1LED35 E4. 1LED40	Standard: W. White Opal Optional: S. Satin White F. Faux Alabaster M. Earth Marble Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBN- Terra Brown TBZ- Textured Bronze	A. No Options B. Top White Perforated Diffuser Top perforated diffuser painted white. C. Bottom White Perforated Diffuser Bottom perforated diffuser painted white. EL. Emergency LED Remote mount up to 5' from lamps in controlled environment with an area temperature of 32"-131°F. LED only. Specify 120 or 277 voltage.

All dimensions are nominal.

Light Source Definition

Lamp	LED	CRI	Rated Life Hrs	Board Lumens	Kelvin
1LED30	11W	80	50000	1855	3000
1LED35	11W	80	50000	1855	3500
1LED40	11W	80	50000	1855	4000

Universal Voltage unless otherwise specified.