

EOS RGB+W

Closed Acrylic Interior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

RGB+White: LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 1% 0-10V dimming standard.

RGB: LED option features RGB color changing light source. RGB channel wired DMX ready.

Static Color: LED options (Red, Green, or Blue) feature static color.

Acrylic: Satin white acrylic is UL-94 HB Flame Class rated.


Cable Hanger: Comes with 72" cable and white cord for on-site adjustability.


Canopy: Painted textured white.

Finish: Highly durable oven cured no VOC premium powder coat.

DMX: Controls by others.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2635-		L-	1-	A
MODEL NO.		LAMPING	HANGER	OPTIONS
GL-2635	W in 26" mm 660 10lbs B in 8" mm 205 4.5kg H in 20"-68" mm 510-1730 Fixture Painted White	G. RED H. GREEN I. BLUE J. RGB* K. RGB30* L. RGB35* M. RGB40*	1. Cable 	A. No Options LC. 150" Cord & Cable Supplied with 150" Cord & Cable. EL. Emergency Ballast Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-2636	W in 37 1/2" mm 950 15lbs B in 8" mm 205 6.8kg H in 20"-68" mm 510-1730 Fixture Painted White	N. RED O. GREEN P. BLUE Q. RGB* R. RGB30* S. RGB35* T. RGB40*		

All Dimensions are nominal.
*DMX controls supplied by others.

Light Source Definition

Fixture	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens
GL-2635	71	+80	50000	7047
GL-2636	113	+80	50000	11802

Universal Voltage unless otherwise specified.