

# EOS RGB+W

## Closed Acrylic Interior Surface Mount



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**RGB+White:** LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 1% 0-10V dimming standard.

**RGB:** LED option features RGB color changing light source. RGB channel wired DMX ready.


**Static Color:** LED options (Red, Green, or Blue) feature static color.

**Acrylic:** Satin white seamless acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**DMX:** Controls by others.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3635-					L-	A-
MODEL NO.					LAMPING	OPTIONS
<b>GL-3635</b>	W in	26"	mm	660	<b>G.</b> RED	<b>A.</b> No Options <b>EL.</b> Emergency Ballast Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
	8lbs B in	8"	mm	205	<b>H.</b> GREEN	
	3.5kg H in	8 3/8"	mm	215	<b>I.</b> BLUE	
Fixture Painted White					<b>J.</b> RGB*	
					<b>K.</b> RGB30*	
					<b>L.</b> RGB35*	
					<b>M.</b> RGB40*	
					<b>N.</b> RED	
					<b>O.</b> GREEN	
					<b>P.</b> BLUE	
<b>GL-3636</b>	W in	37 1/2"	mm	950	<b>Q.</b> RGB*	
	10lbs B in	8"	mm	205	<b>R.</b> RGB30*	
	4.5kg H in	8 3/8"	mm	215	<b>S.</b> RGB35*	
Fixture Painted White					<b>T.</b> RGB40*	

All Dimensions are nominal.  
\*DMX controls supplied by others.

### Light Source Definition

Fixture	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens
GL-3635	71	+80	50000	7047
GL-3636	113	+80	50000	11802

Universal Voltage unless otherwise specified.