


GENERAL SPECIFICATION

LED: High efficiency high-power LEDs. Universal 120-277V input voltage.
LED Dimming: Standard 1% 0-10V dimming.
Body: Cast aluminum.
Diffuser: UL-94 HB Flame Class rated.
Standard Finishes: Highly durable oven cured no VOC premium powder coat.
Surge Protection: External surge protector provided as standard.
Mounting: Driver mounted in 4" square by 2 1/8" deep junction box. Steel City #52171 or equivalent (supplied by others). HO lamping options require remote driver enclosure (supplied). Must be mounted in a controlled environment with an area temperature range of 32°-131°F.
Modified: Contact factory for modified lumen packages.
Listing: Fixture ETL listed for wet locations.



| SAMPLE CATALOG NUMBER: | | | | | | |
|------------------------|--|---|---|---|---|--|
| GL-6610- | | B- | CC- | R5- | PA- | A |
| MODEL NO. | | LAMPING | UPLIGHT | DOWNLIGHT | FINISH | OPTION(S) |
| GL-6610 | W in 4 1/2" mm 115 H in 6" mm 150 E in 4" mm 100 4lbs 1.8kg | A. 1LED30 B. 1LED35 C. 1LED40 *D. 1LED30HO *E. 1LED35HO *F. 1LED40HO *Driver mounted remotely. Enclosure supplied. One lamping code available per fixture. | R2. 20deg R3. 30deg R5. 50deg CC. CLOSED | R2. 20deg R3. 30deg R5. 50deg CC. CLOSED | Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze Premium: SA-Satin Aluminum | A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. |
| GL-6611 | W in 5 3/8" mm 135 H in 12" mm 305 E in 4 3/4" mm 120 6lbs 2.7kg | G. 1LED30 H. 1LED35 I. 1LED40 *J. 1LED30HO *K. 1LED35HO *L. 1LED40HO *Driver mounted remotely. Enclosure supplied. One lamping code available per fixture. | | | | |

All dimensions are nominal.

Light Source Definition

| Specifications per side | | | | | | | Specifications per side | | | | | | |
|-------------------------|----------|---------|-----|----------------|------------------|--------|-------------------------|----------|---------|-----|----------------|------------------|--------|
| CODE | LED | Wattage | CRI | Rated Life Hrs | Delivered Lumens | Kelvin | CODE | LED | Wattage | CRI | Rated Life Hrs | Delivered Lumens | Kelvin |
| A | 1LED30 | 9W | +80 | 50000 | 1025 | 3000 | G | 1LED30 | 13W | +80 | 50000 | 1426 | 3000 |
| B | 1LED35 | 9W | +80 | 50000 | 1025 | 3500 | H | 1LED35 | 13W | +80 | 50000 | 1426 | 3500 |
| C | 1LED40 | 9W | +80 | 50000 | 1025 | 4000 | I | 1LED40 | 13W | +80 | 50000 | 1426 | 4000 |
| D* | 1LED30HO | 13W | +80 | 50000 | 1426 | 3000 | J* | 1LED30HO | 22W | +80 | 50000 | 2185 | 3000 |
| E* | 1LED35HO | 13W | +80 | 50000 | 1426 | 3500 | K* | 1LED35HO | 22W | +80 | 50000 | 2185 | 3500 |
| F* | 1LED40HO | 13W | +80 | 50000 | 1426 | 4000 | L* | 1LED40HO | 22W | +80 | 50000 | 2185 | 4000 |

Universal Voltage unless otherwise specified.

*Driver Mounted Remotely