

HELIO

Outer Acrylic Interior Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.


Acrylic: Satin white seamless outer acrylic is UL-94 HB Flame Class rated.




Cable Hanger: Comes with 72" cable and white cord for on-site adjustability.

Canopy: Painted textured white.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2651-				B-	1-	A
MODEL NO.				LAMPING	HANGER	OPTIONS
GL-2650	W in 26" mm 660	20lbs B in 8 1/2" mm 215	9kg H in 20"-68" mm 510-1730	M. 4LED30 F. 4LED35 N. 4LED40	1. Cable - Standard 	A. No Options LC. 150" Cord & Cable Supplied with 150" Cord & Cable. EL. Emergency Ballast Integrally operates two LED strips. Integral test switch. Specify voltage after code.
GL-2651	W in 37 1/2" mm 950	30lbs B in 8 1/2" mm 215	13.5kg H in 20"-68" mm 510-1730	C. 6LED30 B. 6LED35 E. 6LED40	2. Vertical Cable 	
GL-2652	W in 52" mm 1320	40lbs B in 8 1/2" mm 215	18kg H in 20"-68" mm 510-1730	I. 10LED30 J. 10LED35 R. 10LED40	3. Vertical Cable 	

GL-2650 & GL-2651 (3) Canopies total.

GL-2652 (4) Canopies total.

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
4LED30	56W	3837	3000
4LED35	56W	3837	3500
4LED40	56W	3837	4000
6LED30	85W	6374	3000
6LED35	85W	6374	3500
6LED40	85W	6374	4000
10LED30	141W	10840	3000
10LED35	141W	10840	3500
10LED40	141W	10840	4000

Universal Voltage unless otherwise specified.