

HUDSON

Indoor Surface Mount





9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs are field serviceable.
- LED Dimming:** 1% 0-10V dimming standard with LED lamping option.
- Body:** GL-3260-3262 ring spun in 18ga steel or .050 aluminum.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3262-		L45-	S-	NSN-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)	
GL-3260 14lbs B in 18" mm 460 6 kg W in 24" mm 610 D in 8" mm 200	F4. 4CF26 L30. 3LED30 IN3. 3MED* L35. 3LED35 L34. 3LED40	Standard: S. Satin White Optional: W. White Opal F. Faux Alabaster M. Earth Marble Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze Premium: SB-Satin Brass PB-Polished Brass AB-Antique Brass ORB-Oil Rubbed Bronze PC-Polished Copper SA-Satin Aluminum SN-Satin Nickel	A. No Options F. Add Finial  B. Damp Location Available in powder coat or Satin Aluminum finish. DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Ballast Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°-131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. Multi-circuiting available upon request.	
GL-3261 21lbs B in 24" mm 610 10 kg W in 30" mm 765 D in 9" mm 230	F4. 4CF26 L40. 4LED30 IN3. 3MED* L45. 4LED35 L44. 4LED40				
GL-3262 29lbs B in 30" mm 760 13kg W in 36" mm 915 D in 10" mm 255	F4. 4CF26 L40. 4LED30 IN6. 6MED* L45. 4LED35 L44. 4LED40 L60. 6LED30 L65. 6LED35 L64. 6LED40				

*120 Volt Only

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Light Source Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens ¹	Code	Total Wattage	Kelvin	Delivered Lumens
F4, F6	CF	CF 26W/32W/42W	GX24q-3 4PIN	1530/2040/2690	L30	42	3000	4211
IN3, IN6	Med	A-19	Medium		L35	42	3500	4211
					L34	42	4000	4211
					L40	58	3000	5074
					L45	58	3500	5074
					L44	58	4000	5074
					L60	87	3000	8063
					L65	87	3500	8063
					L64	87	4000	8063

¹Per MAXLTE & GE lamp products catalog
Contact factory for availability of other lamp configurations including induction and metal halide.

Universal Voltage unless otherwise specified.

