

# LUNA

## Interior Surface Mount




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@lighting.com www.lighting.com

### GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.  
LED Dimming: Standard 1% 0-10V dimming.  
Driver: Integral in fixture body. Remote driver required for V,W,X lamping options.  
Acrylic: Acrylic is UL-94 HB Flame Class rated.  
Finish: Highly durable oven cured no VOC premium powder coat.  
Surge Protection: External surge protector provided as standard.



### SAMPLE CATALOG NUMBER:

GL-3375-

MODEL NO.	E- LAMPING	BLK- FINISH	A OPTIONS
<b>GL-3375</b> W 16 in 8lbs H 10 7/8 in 3.6kg	A. 1LED30 B. 1LED35 C. 1LED40 D. 1LED30 E. 1LED35 F. 1LED40 G. 1LED30 H. 1LED35 I. 1LED40 V. 1LED30* W. 1LED35* X. 1LED40*	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue  <b>Textured Powder</b> TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze  <b>Premium:</b> SA-Satin Aluminum	<b>A. No Options</b>  <b>DM. DMX Dimming</b> Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F.  <b>EL. Emergency LED</b> Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.

\*Remote Driver only.

All Dimensions are nominal.

### Light Source Definition

Code	LED	Downlight Output		Kelvin	CRI	
		Total Wattage	Delivered Lumens			
A	1LED30	15W	1538	3000	80	
B	1LED35	15W	1538	3500	80	
C	1LED40	15W	1538	4000	80	
D	1LED30	26W	2637	3000	80	
E	1LED35	26W	2637	3500	80	
F	1LED40	26W	2637	4000	80	
G	1LED30	39W	3956	3000	80	
H	1LED35	39W	3956	3500	80	
I	1LED40	39W	3956	4000	80	
V	1LED30	68W	6009*	3000	80	
W	1LED35	68W	6009*	3500	80	
X	1LED40	68W	6009*	4000	80	*Projected

Universal Voltage unless otherwise specified.  
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

