MARINA II WARM DIM

Interior Round Pendant

9777 Reavis Park Drive St. Louis, MO 63123 800.331.2425 or 314.631.6000

GENERAL SPECIFICATION

Warm Dim: LED option (WD) features warm dimming technology that dims

smoothly from 3500K-1800K with standard 0-10V dimming.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

Shade: Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.

Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.

Cable Hanger Option: Supplied with standard 72" white cord and cable. Field

adjustable.

Finish: Highly durable oven cured no VOC premium powder coat. **Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:									
GL-2742	?-	WD5-	W-	NSN-	5-	A-	072		
MODEL	NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALI HEIGHT		
GL-2742 W in 2 15lbs D in 1 ⁻⁷ kg H Sp	1.5"	WD5	S Stone Washable:	PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne	5. Cord & Cable Supplied with white cord with hanger option 5.	Must be remotely mounted in a controlled environment with an area temperature range of	in inches.		
GL-2743 W in 3 18lbs D in 12 8kg H Sp	2.5"	WD5				32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.			
GL-2744 W in 3 20lbs D in 13 9kg H Sp	3.5"								
GL-2745 W in 4 25lbs D in 15 11.5kg H Sp	5.5"	WD8							

All Dimensions are nominal.

Shade

Standard

White Cream Blue Stone Red Olive

Washable - Trilam

White Tan Cream Brown

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

	Total	Delivered	
<u>Code</u>	<u>Wattage</u>	<u>Lumens</u>	<u>Kelvin</u>
WD5	107	7736	3500-1800
WD8	170	12248	3500-1800

Universal Voltage unless otherwise specified.