

# MARINA II WARM DIM

## Interior Round Semi-Surface Mount



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**Warm Dim:** LED option (WD) features warm dimming technology that dims smoothly from 3500K-1800K with standard 1% 0-10V dimming.


**LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

**Shade:** Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.

Standard textured white finish



SAMPLE CATALOG NUMBER: GL-3742-		WD5-	W-	A
MODEL NO.		LAMPING	SHADE	OPTIONS
<b>GL-3742</b>	W in 24" mm 610 15lbs D in 11.5" mm 295 7kg	WD5	W White C Cream R Red BL Blue O Olive S Stone	<b>A.</b> No Options <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.
<b>GL-3743</b>	W in 30" mm 760 18lbs D in 12.5" mm 320 8kg	WD5	Washable: WW White WC Cream WT Tan WB Brown	
<b>GL-3744</b>	W in 36" mm 915 20lbs D in 13.5" mm 340 9kg	WD8		
<b>GL-3745</b>	W in 48" mm 1220 25lbs D in 15.5" mm 395 11.5kg	WD8		

All Dimensions are nominal.

### Shade

Standard											
	White		Cream		Blue		Stone		Red		Olive
Washable - Trilam											
	White		Tan		Cream		Brown				

Custom fabrics available upon request. Contact factory.  
Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
WD5	107	7736	3500-1800
WD8	170	12248	3500-1800

Universal Voltage unless otherwise specified.