

MARINA II

Interior Round Semi-Surface Mount




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs are field serviceable.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Dimming:** 1% 0-10V dimming standard.
- Shade:** Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for lamping or cluster options.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:				L55-		W-		A	
GL-3742-				LAMPING		SHADE		OPTIONS	
MODEL NO.									
GL-3740	W in 14"	mm 355	5lbs 2.25kg	IN3. 3MED*	L10. 1LED30 L15. 1LED35 L14. 1LED40	LL10. 1LED30LO LL15. 1LED35LO LL14. 1LED40LO	W White C Cream R Red BL Blue O Olive S Stone	A. No Options DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°-131°F. Compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.	
GL-3741	W in 18"	mm 460	5lbs 2.25kg	IN3. 3MED*	L10. 1LED30 L15. 1LED35 L14. 1LED40	LL10. 1LED30LO LL15. 1LED35LO LL14. 1LED40LO	Washable: WW White WC Cream WT Tan WB Brown		
GL-3742	W in 24"	mm 610	15lbs 7kg	IN3. 3MED* F4. 4CF	L50. 5LED30 L55. 5LED35 L54. 5LED40	LL50. 5LED30LO LL55. 5LED35LO LL54. 5LED40LO			
GL-3743	W in 30"	mm 760	18lbs 8kg	IN3. 3MED* F4. 4CF	L50. 5LED30 L55. 5LED35 L54. 5LED40	LL50. 5LED30LO LL55. 5LED35LO LL54. 5LED40LO			
GL-3744	W in 36"	mm 915	20lbs 9kg	IN6. 6MED* F6. 6CF	L80. 8LED30 L85. 8LED35 L84. 8LED40	LL80. 8LED30LO LL85. 8LED35LO LL84. 8LED40LO			
GL-3745	W in 48"	mm 1220	25lbs 11.5kg	IN6. 6MED* F6. 6CF	L80. 8LED30 L85. 8LED35 L84. 8LED40	LL80. 8LED30LO LL85. 8LED35LO LL84. 8LED40LO			

All Dimensions are nominal.

Shade

Standard

White Cream Blue Stone Red Olive

Washable - Trilam

White Tan Cream Brown

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens	Code	Lamp	Total Wattage	Delivered Lumens	Kelvin
F4,F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690	LL50	5LED30LO	43W	4462*	3000
IN3,IN6	MED	A-19	Medium		LL55	5LED35LO	43W	4462*	3500
					LL54	5LED40LO	43W	4462*	4000
					L50	5LED30	72W	7436	3000
					L55	5LED35	72W	7436	3500
					L54	5LED40	72W	7436	4000
					LL80	8LED30LO	69W	7126*	3000
					LL85	8LED35LO	69W	7126*	3500
					LL84	8LED40LO	69W	7126*	4000
					L80	8LED30	114W	12248	3000
					L85	8LED35	114W	12248	3500
					L84	8LED40	114W	12248	4000

*Projected Lumen Output

Universal Voltage unless otherwise specified.