

MEDI

Interior Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs.
Uplight: Optional uplight is wired on a second circuit. Standard satin white top lens.
LED Dimming: Standard 1% 0-10V dimming.
Cable Hanger Option: Standard 150" cable and white cord for on-site adjustability.
Canopy: Matches outer fixture finish. Hanger 3 & 4 with A-O lamping option includes 9.125" dia by 2.625" H spinning. V, W, X lamping includes 12.5" dia by 2" H.
Driver: Max remote driver installation distance 25ft from fixture body.
Acrylic: Acrylic is UL-94 HB Flame Class rated.
Finish: Highly durable oven cured no VOC premium powder coat.
Inner Finish: Inner finish matches outer finish.
Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:								
GL-2356-		E-	K-	BLK-	MO-	1-	A	038
MODEL NO.	LAMPING	UPLIGHT	OUTER FINISH	INNER FINISH	HANGER	OPTIONS	OVERALL HEIGHT	
GL-2355 8lbs W in 16" 3.6kg B in 7 3/8" H in 38"	A. 1LED30	NA. NONE	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue	Standard: MO-Matches Outer Finish Liquid Paint WH-White BLK-Black GL-Gold	1. Stem Mount Remote Driver Drivers mounted remotely 2. Cable Mount Remote Driver Drivers mounted remotely 3. Stem Mount Oversized Canopy Drivers mounted inside oversized canopy 4. Cable Mount Oversized Canopy Drivers mounted inside oversized canopy	A. No Options BC. Black Cord Fixture supplied with black power cord. DM. DMX Dimming EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. Downlight only.	Specify overall height in inches for hanger styles 1 & 3.	
	GL-2356 10lbs W in 24" 4.5kg B in 11 9/16" H in 42"	J. 1UPLED30 K. 1UPLED35 L. 1UPLED40 M. 1UPLED30 N. 1UPLED35 O. 1UPLED40 G. 1LED30 H. 1LED35 I. 1LED40 V. 1LED30* W. 1LED35* X. 1LED40*						
GL-2357 15lbs W in 32" 6.8kg B in 15 11/16" H in 46"								

All Dimensions are nominal.

Light Source Definition

Downlight Output						Uplight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	1LED30	15W	1538	3000	80	J	1UPLED30	8W	866	3000	80
B	1LED35	15W	1538	3500	80	K	1UPLED35	8W	866	3500	80
C	1LED40	15W	1538	4000	80	L	1UPLED40	8W	866	4000	80
D	1LED30	26W	2637	3000	80	M	1UPLED30	12W	1213	3000	80
E	1LED35	26W	2637	3500	80	N	1UPLED35	12W	1213	3500	80
F	1LED40	26W	2637	4000	80	O	1UPLED40	12W	1213	4000	80
G	1LED30	39W	3956	3000	80						
H	1LED35	39W	3956	3500	80						
I	1LED40	39W	3956	4000	80						
V	1LED30	68W	6009*	3000	80						
W	1LED35	68W	6009*	3500	80						
X	1LED40	68W	6009*	4000	80						

*Projected

Universal Voltage unless otherwise specified. Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.