MONTEREY

Interior ADA Fabric Sconce

9777 Reavis Park Drive St. Louis, MO 63123 800.331.2425 or 314.631.6000

GENERAL SPECIFICATION

Shade: Standard white fabric shade. Custom shapes, sizes, and colors available.

Lamping: Standard lamping packages offer long lamp life, high power factor

energy efficient electronic driver. 1% 0-10v dimming standard.

Acrylic: UL-94 HB Flame Class rated. Standard white opal top and bottom lens.


Standard Finish: Highly durable oven cured no VOC premium powder coat.

Custom: Contact factory for custom lengths and lamping.

LED: Driver mounted in 4" square x 2 1/8" deep junction box:

Steel City #52171 or equivalent (supplied by others)

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:								
GL-4705-	B-	W-	NSN-	A				
MODEL NO.	LAMPING	SHADE	FINISH	OPTION(S)				
GL-4705 W in 6" mm 150 H in 12 5/8" mm 330 4lbs 1.8kg D in 3 7/8" mm 100	A. 14LED30 B. 14LED35 C. 14LED40	W White C Cream R Red BL Blue O Olive	Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. TD. Triac/ELV Dimming				
GL-4706 W in 7" mm 175 H in 18" mm 460 5lbs 2.3kg D in 3 7/8" mm 100	A. 14LED30 B. 14LED35 C. 14LED40	S Stone Washable: WW White WC Cream WT Tan WB Brown						

All dimensions are nominal.

Shade

S	<u>Standard</u>												
		White		Cream		Blue		Stone		Red		Olive	
Washable - Trilam													
		White		Tan		Cream		Brown	Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales @elighting.com for fabric samples.				
												·	

Lamp Definition

				Rated	Delivered
<u>Lamp</u>	<u>LED</u>	Kelvin	<u>CRI</u>	Life Hrs	<u>Lumens</u>
14LED30	14W	3000	80	50000	1169
14LED35	14W	3500	80	50000	1169
14LED40	14W	4000	80	50000	1169

Universal Voltage unless otherwise specified.