

# OCULUS RGB+W

## Interior Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**RGB+White:** LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 1% 0-10V dimming standard.

**RGB:** LED option features RGB color changing light source. RGB channel wired DMX ready.

**Static Color:** LED options (Red, Green, or Blue) feature static color.

**Acrylic:** Satin white seamless acrylic is UL-94 HB Flame Class rated.


**Cable Hanger:** Comes with 72" cable and cord for on-site adjustability.

**Canopy:** Matches fixture finish.

**Finish:** Highly durable oven cured no VOC premium powder coat. Spinning interior painted textured white.

**DMX:** Controls by others.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:				
GL-2641-				
MODEL NO.	S-	PTC-	1-	A
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS
<b>GL-2640</b> W in 26" mm 660 10lbs B in 7 1/2" mm 190 4.5kg H in 20"-68" mm 510-1730	<b>G. RED</b> <b>H. GREEN</b> <b>I. BLUE</b> <b>J. RGB*</b> <b>K. RGB30*</b> <b>L. RGB35*</b> <b>M. RGB40*</b>	Standard: Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze Textured Powder <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBN</b> -Terra Brown <b>TBZ</b> -Textured Bronze Premium: <b>SA</b> -Satin Aluminum Not available in standard white finish	<b>1. Cable</b> 	<b>A. No Options</b> <b>BC. Black Cord</b> Fixture supplied with black power cord. <b>LC. 150" Cord &amp; Cable</b> Fixture supplied with 150" of cable and standard white cord or optional black cord. <b>EL. Emergency LED</b> Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-2641</b> W in 37" mm 940 15lbs B in 7 1/2" mm 190 6.8kg H in 20"-68" mm 510-1730	<b>N. RED</b> <b>O. GREEN</b> <b>P. BLUE</b> <b>Q. RGB*</b> <b>R. RGB30*</b> <b>S. RGB35*</b> <b>T. RGB40*</b>	Standard: Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze Textured Powder <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBN</b> -Terra Brown <b>TBZ</b> -Textured Bronze Premium: <b>SA</b> -Satin Aluminum Not available in standard white finish	<b>1. Cable</b> 	<b>A. No Options</b> <b>BC. Black Cord</b> Fixture supplied with black power cord. <b>LC. 150" Cord &amp; Cable</b> Fixture supplied with 150" of cable and standard white cord or optional black cord. <b>EL. Emergency LED</b> Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.

All Dimensions are nominal.  
\*DMX controls supplied by others

### Light Source Definition

Fixture	Total Wattage	Rated CRI	Rated Life Hrs	Delivered Lumens
GL-2640	57W	+80	50000	4310
GL-2641	72W	+80	50000	5320

Universal Voltage unless otherwise specified.