

OCULUS WARM DIM

Interior Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Warm Dim: LED option (WD) features warm dimming technology that dims smoothly from 3500K-1800K with standard 1% 0-10V dimming.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.


Acrylic: Satin white seamless acrylic is UL-94 HB Flame Class rated.

Cable Hanger: Comes with 72" cable and cord for on-site adjustability.

Canopy: Matches fixture finish.

Finish: Highly durable oven cured no VOC premium powder coat. Spinning interior painted textured white.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2641-		WD5-	PTC-	1-	A
MODEL NO.		LAMPING	FINISH	HANGER	OPTIONS
GL-2640 W in 26" mm 660 10lbs B in 7 1/2" mm 190 4.5kg H in 20"-68" mm 510-1730		WD4	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBN -Terra Brown TBZ -Textured Bronze Premium: SA -Satin Aluminum Not available in standard white finish	1. Cable 	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32"-131°F. Specify 120 or 277 voltage.
GL-2641 W in 37" mm 940 15lbs B in 7 1/2" mm 190 6.8kg H in 20"-68" mm 510-1730					

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
WD4	82W	4310	3500-1800
WD5	108W	5320	3500-1800

Universal Voltage unless otherwise specified.