

# OCULUS

## Interior Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs are field serviceable.

**LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.


**Acrylic:** Satin white seamless acrylic is UL-94 HB Flame Class rated.

**Cable Hanger:** Comes with 72" cable and cord for on-site adjustability.

**Canopy:** Matches fixture finish.

**Finish:** Highly durable oven cured no VOC premium powder coat. Spinning interior painted textured white.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2641-		E-	PTC-	1-	A
MODEL NO.		LAMPING	FINISH	HANGER	OPTIONS
<b>GL-2640</b>	W 26" in 660 mm 10lbs B 7 1/2" in 190 mm 4.5kg H 20"-68" in 510-1730 mm	<b>A.</b> 4LED30 <b>B.</b> 4LED35 <b>C.</b> 4LED40	Standard: Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze  Textured Powder <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBN</b> -Terra Brown <b>TBZ</b> -Textured Bronze  Premium: <b>SA</b> -Satin Aluminum  Not available in standard white finish	<b>1. Cable</b> 	<b>A.</b> No Options <b>BC.</b> Black Cord Fixture supplied with black power cord. <b>LC.</b> 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. <b>EL.</b> Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32"-131°F. Specify 120 or 277 voltage.
<b>GL-2641</b>	W 37" in 940 mm 15lbs B 7 1/2" in 190 mm 6.8kg H 20"-68" in 510-1730 mm	<b>D.</b> 5LED30 <b>E.</b> 5LED35 <b>F.</b> 5LED40			

All Dimensions are nominal.

### Light Source Definition

Code	Total Wattage	Rated CRI	Rated Life Hrs	Delivered Lumens	Kelvin
4LED30	57W	+80	50000	4310	3000
4LED35	57W	+80	50000	4310	3500
4LED40	57W	+80	50000	4310	4000
5LED30	72W	+80	50000	5320	3000
5LED35	72W	+80	50000	5320	3500
5LED40	72W	+80	50000	5320	4000

Universal Voltage unless otherwise specified.