OCULUS RGB+W

Interior Surface Mount

G Lighting
9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000
sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

RGB+White: LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 1% 0-10V dimming standard.

RGB: LED option features RGB color changing light source. RGB channel wired DMX ready.

Static Color: LED options (Red, Green, or Blue) feature static color.

Acrylic: Satin white seamless acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat. Spinning interior painted textured white.

Surge Protection: External surge protector provided as standard.

DMX: Controls by others.



SAMPLE CATALOG NUMBER:
GL-3641- S- NSN- A

MODEL NO.	LAMPING	FINISH	OPTIONS
GL-3640 W in 26" mm 660 8lbs B in 7 1/2" mm 190 3.5kg	**G.** RED **H.** GREEN **I.** BLUE **J.** RGB* **K.** RGB30* **L.** RGB35* **M.** RGB40*	Standard: Powder Coat **BLK**-Black **BL**-Blue **GR**-Gray **LG**-Light Gray **BE**-Beige **PAB**-Antique Brass **PA**-Painted Aluminum **PTC**-Painted Copper **DBZ**-Dark Bronze **NSN**-New Satin Nickel **BRN**-Brown **RD**-Red **CH**-Champagne **RG**-Reed Green **SG**-Sungold **GM**-Gun Metal **POR**-Oil Rubbed Bronze Textured Powder **TLV**-Light Verdigris **TWH**-Textured White **TBL**-Textured Black **TS**-Textured Silver **TBN**-Terra Brown **TBZ**-Textured Bronze Premium: **SA**-Satin Aluminum **Not available in standard white finish**	**A.** No Options **EL.** Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-3641 W in 37" mm 940 10lbs B in 7 1/2" mm 190 4.5kg	**N.** RED **O.** GREEN **P.** BLUE **Q.** RGB* **R.** RGB30* **S.** RGB35* **T.** RGB40*		

All Dimensions are nominal.
*DMX controls supplied by others

Light Source Definition

Fixture	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens
GL-3640	57W	+80	50000	4310
GL-3641	72W	+80	50000	5320

Universal Voltage unless otherwise specified.

© Gross Chandelier Co.

G Lighting reserves the right to modify existing designs to improve appearance or function

G Lighting products are union made.