


GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs are field serviceable.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
- Acrylic:** Satin white seamless acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat. Spinning interior painted textured white.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3641-		E-	NSN-	A
MODEL NO.		LAMPING	FINISH	OPTIONS
GL-3640 W 26" in 660 mm 8lbs B 7 1/2" in 190 mm 3.5kg		A. 4LED30 B. 4LED35 C. 4LED40	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBN -Terra Brown TBZ -Textured Bronze Premium: SA -Satin Aluminum Not available in standard white finish	A. No Options EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
4LED30	57W	+80	50000	4310	3000
4LED35	57W	+80	50000	4310	3500
4LED40	57W	+80	50000	4310	4000
5LED30	72W	+80	50000	5320	3000
5LED35	72W	+80	50000	5320	3500
5LED40	72W	+80	50000	5320	4000

Universal Voltage unless otherwise specified.