

EDITOR

Interior Schoolhouse Sconce





9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED: High efficiency mid-power LEDs are field serviceable.
- LED Dimming: 1% 0-10V dimming standard with LED lamping option.
- Body: 18ga steel or .050 aluminum glass fitter.
- Glass: White opal diffuser hand blown in the USA.
- Finish: Highly durable oven cured no VOC premium powder coat.
- Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-4300-				
MODEL NO.	L5-	A-	SN-	A-
MODEL NO.	LAMPING	GLASS	FINISH	OPTION(S)
GL-4300	L0. 11LED30 L5. 11LED35 L4. 11LED40 Driver in backplate	A. Editor Glass	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze Premium: SA-Satin Aluminum	A. No Options B. Damp Location Available in powder coat or Satin Aluminum finish. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.
GL-4301	IN1. 1MED 120 volt only			

All dimensions are nominal.

Light Source Definition

Code	LED	Kelvin	Rated Life Hrs	Lumens
11LED30	11W LED	3000	50000	1460
11LED35	11W LED	3500	50000	1460
11LED40	11W LED	4000	50000	1460

Universal Voltage unless otherwise specified.