

# SELENE RGB+W

## Inner Acrylic Interior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**RGB+White:** LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 0-10V dimming standard.

**RGB:** LED option features RGB color changing light source. RGB channel wired DMX ready.

**LED Dimming:** Standard 0-10V dimming. TRIAC, DALI, or DMX available upon request.

**Acrylic:** Satin white seamless outer acrylic is UL-94 HB Flame Class rated.


**Cable Hanger:** Comes with 72" cable and cord for on-site adjustability.

**Canopy:** Matches fixture finish.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Body:** Ring spun in 1/8" aluminum.

**DMX:** Controls by others.



### SAMPLE CATALOG NUMBER:



GL-2581-

AA-

PTC-

1-

A-

MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS
<b>GL-2580</b> W in 26" mm 660 20lbs B in 7 1/2" mm 190 9kg H in 20"-68" mm 510-1730  Fixture supplied with 72" of cord and cable. Adjust on-site. Minimum 20" OAH. Contact factory for OAH greater than 68".	<b>O. RED</b> <b>P. GREEN</b> <b>Q. BLUE</b> <b>R. RGB*</b> <b>S. RGB30*</b> <b>T. RGB35*</b> <b>U. RGB40*</b>	<b>Standard:</b> <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze  <b>Textured Powder</b> <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBN</b> -Terra Brown <b>TBZ</b> -Textured Bronze	<b>1. Cable</b>   <b>2. Vertical Cable</b> 	<b>A. No Options</b> <b>EL. Emergency Ballast</b> Integrally operates two LED strips. Integral test switch. Specify voltage after code. Available GL-2581 only. <b>BC. Black Cord</b> Fixture supplied with black power cord. <b>LC. 150" Cord &amp; Cable</b> Supplied with 150" Cord & Cable.
<b>GL-2581</b> W in 37" mm 940 30lbs B in 7 1/2" mm 190 13.5kg H in 20"-68" mm 510-1730  Fixture supplied with 72" of cord and cable. Adjust on-site. Minimum 20" OAH. Contact factory for OAH greater than 68".	<b>V. RED</b> <b>W. GREEN</b> <b>X. BLUE</b> <b>Y. RGB*</b> <b>Z. RGB30*</b> <b>AA. RGB35*</b> <b>BB. RGB40*</b>			

All Dimensions are nominal.

\*DMX controls supplied by others.

### Light Source Definition

Fixture	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens
GL-2580	85	+80	50000	3837
GL-2581	113	+80	50000	6374

Universal Voltage unless otherwise specified.