

SIDNEY 10" LED

Interior Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.
LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
Down Light: 90CRI 17 watt 2000 lumen module. Lamping code ending with "DL" includes downlight.
Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.
Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.
Cable Hanger Option: Supplied with standard 72" white cord and cable. Field adjustable.
Finish: Highly durable oven cured no VOC premium powder coat.
Modifications: Consult factory for lamping or cluster options.
Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2680 W in 10" mm 255 B in 28" mm 710 15lbs H in 38" mm 965 7kg Fixture does not include downlight	I. 4LED30 J. 4LED35 K. 4LED40	Standard: W White Opal S Satin White Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBN -Terra Brown TBZ -Textured Bronze	1. Stem Remote driver. 2. Cable Standard white power cord. Remote driver. 3. Oversized with Stem 12.5" Canopy 4. Oversized with Cable Standard white power cord. 12.5" Canopy.	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32"-131°F. Specify 120 or 277 voltage.	Stem mount only - Specify overall height in inches. Standard overall height shown by model no.
GL-2681 W in 10" mm 255 B in 32 1/4" mm 820 15lbs H in 42" mm 1065 7kg Fixture includes downlight	L. 4LED30DL M. 4LED35DL N. 4LED40DL					
GL-2682 W in 10" mm 255 B in 51 3/4" mm 1315 30lbs H in 62" mm 1575 13.5kg Fixture does not include downlight	O. 4LED30 P. 4LED35 Q. 4LED40					
GL-2683 W in 10" mm 255 B in 55 7/8" mm 1420 30lbs H in 66" mm 1675 13.5kg Fixture includes downlight	R. 4LED30DL S. 4LED35DL T. 4LED40DL		Premium: SA -Satin Aluminum		Hanger options 1&2 supplied with remote driver box.	

Light Source Definition

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Code	Total Wattage	Delivered Lumens	Kelvin	Code	*Total Wattage	*Delivered Lumens	Kelvin
I	51W	5556	3000	L	68W	7248	3000
J	51W	5556	3500	M	68W	7248	3500
K	51W	5556	4000	N	68W	7248	4000
O	104W	11091	3000	R	121W	12783	3000
P	104W	11091	3500	S	121W	12783	3500
Q	104W	11091	4000	T	121W	12783	4000

Universal Voltage unless otherwise specified.

*Includes downlight wattage (17W) and lumen output (1692lm)

