CP3990 OMNIENCE™

48" Diameter - Stem



Visalighting.com/products/0mnience

Type: Project: Location:





DIMENSIONS⁴


STRUCTURAL BLOCKING REQUIRED (DETAIL PAGE 2)

A OAH must be specified

OAH is the distance (in inches) from the bottom of the fixture to the ceiling plane. Example - OAH(42) indicates an overall fixture height of 42".

W = Width X = Body Height OAH = Standard Overall Height


W 48" (1219 mm) OAH 42" (1066 mm) X 6-3/4" (171 mm)




FEATURES

- Integral driver
- Modular design for replacement of LED source and driver
- Upper perforations provide a luminous glow to reduce ceiling contrast if UPLT option is selected
- Mounts through 4" octagonal 2-1/8" deep electrical junction box (by others) with provided hardware for ceiling slopes up to 45° from horizontal
- Rolled extruded aluminum housing
- 1/8" thick diffuser with matte finish
 - UV stable
- Optional specialty diffuser materials available, including Vara Kamin's Impressions of Light® images which are replicated from Vara Kamin's original works of art
- Optional 1/8" thick impact resistant polycarbonate clear lens cover
- No VOC powder coat paint; Low VOC clear coat on metal finishes
- ETL listed for damp locations. Not suitable for exterior applications

RELATIVE SCALE DRAWING



PHOTOMETRICS









XPS

J lear warranty

CP3990 OMNIENCE (cont.)

48" Diameter - Stem



Fill in shaded boxes using information listed below CP3990 **MVOLT** MODEL SOURCE1 **VOLTAGE FINISH** DIFFUSER² OPTION(S)3 OAH4 • L30K OPTION **UPLT** MVOLT See page 1 See last page L35K IRP XPS for finish • VKMD • L40K order codes VKMM • VKPG VKSS

SOURCE¹ (Select one)

Dimmable 0-10V to 1%, Minimum 83CRI within 3-step MacAdam

Sources	ССТ	Delivered Lumens	Power (Watts)
• L30K	3000K	13400	157
L35K	3500K	13400	157
• L40K	4000K	13800	157

VOLTAGE

MVOLT	120-277V, 50/60 Hz
-------	--------------------

DIFFUSER OPTIONS²

Diffuser is matte white acrylic if no option is selected

IRP	Impact resistant polycarbonate lens		
• VKMD	Vara Kamin's Moon Drops®		
• VKMM	Vara Kamin's Morning Melody®	VKMB VKMB VKPG VKSS	
• VKPG	Vara Kamin's Priscilla's Garden®	Vara Kamin options have been color-corrected to	
• VKSS Vara Kamin's Summer of Sundays®		4000K CCT and are available only with L40K source.	

OPTIONS³ (Multiple selections allowed)

Option availability may be interdependent with 0ther 0ptions

UPLT	Lensed aperture in housing produces 3.8% uplight	
XPS	Express 10 day shipping. Items marked with a bullet (•) are not available with XPS	

STRUCTURAL BLOCKING DETAIL



CP3990 OMNIENCE (cont.)

48" Diameter - Stem



OMNIENCE PRODUCT FAMILY

Aircraft Cable	26" Diameter	• CP3970
	34" Diameter	• CP3975
	48" Diameter	• CP3995
Stem	26" Diameter	• CP3980
	34" Diameter	• CP3985
	48" Diameter	• CP3990
Ceiling Mount	26" Diameter	• CM1830

See Visalighting.com/products/Omnience for more information

SUGGESTED VARIATIONS

- · Remote driver
- Custom colors

FINISHES

Specify color code when ordering. For accurate color matching, individual paint and finish samples are <u>available upon request</u>. For more information about our finishes visit <u>visalighting.com/finishes</u>

Powder Coat Paint Finishes (Standard)



Wood Sublimated Metal Finishes (Premium)



Lens frame, canopy, and stem are painted white when Wood Sublimated Finish is selected.

This document contains information which is the property of Visa Lighting, and may not, in whole or in part, be duplicated, disclosed, or used for design or manufacturing purposes without the prior written permission of Visa Lighting. ©Visa Lighting. Design Modification Rights Reserved. Visa Lighting reserves the right to change specifications for product improvement without notification.