

Fixture Type: \_\_\_\_\_

Model Number: \_\_\_\_\_

Project Name: \_\_\_\_\_




## SOLITAIRE - OPEN FACE

### Decorative Round LED Surface Bulkhead



#### Dimensions

**Diameter (D)** 12½" (318mm)  
**Height (A)** 3<sup>15</sup>/<sub>16</sub>" (100mm)



**General:** The Solitaire decorative round LED surface bulk head is perfect for areas where good illumination in a decorative package is desired. Designed to replace 100 watt HID lighting systems. The open door frame allows for maximum light output. Typical applications include shopping malls, office buildings, schools, condominiums, and hospitality. Recommended mounting heights: 8' to 20'.

**Housing:** Die cast aluminum housing with fully gasketed cast aluminum open front face frame. Integral heat sinking and driver compartment. Nickel plated stainless steel hardware.

**Lens:** Supplied with polycarbonate opal lens to eliminate LED "hot spots". Type IV distribution.

**Mounting:** Surface mounted.

**LED Board:** Aluminum board with LED array. Available color temperatures of 3000K, 4000K, and 5000K.

**Wattage:** Array: 17.0 watts      System: 19.7 watts

**Driver:** Electronic dimmable driver (525mA)  
120-277V; 50/60Hz

**Options:** Battery Backup (-EM)  
Single Fuse (-SF); Double Fuse (-DF)  
Surge Protector (-SP)  
120v Photocell (-P1); 277v Photocell (-P2)  
Microwave Sensor w/Dimming (internal) (-S2)

**Finish:** Architectural powdercoat finish over a chromate conversion coating. Available in bronze(-BRZ) or white (-WHT) finishes. For custom color (-CC) options, consult factory.

**Certifications:** CSA listed for wet locations  
ANSI / UL 1598, 8750  
Operating temperature: -40°C to +50°C  
ADA Compliant  
IP67 | sealed LED compartment

#### Photometric Performance

LED Board Watts	Drive Current (mA)	Input Watts	Optics	5000 CCT 80 CRI					4000 CCT 80 CRI					3000 CCT 80 CRI				
				Lumens	LPW	B	U	G	Lumens	LPW	B	U	G	Lumens	LPW	B	U	G
LED 17w	525	20	Type IV	2,323	116	1	1	0	2,230	112	1	1	0	2,056	103	1	1	0



IP 67



content of specification sheet is subject to change.

N60 W14592 Kaul Avenue  
Menomonee Falls, WI 53051

P 877 965 0005  
intrigueled.com

Fixture Type: \_\_\_\_\_

Model Number: \_\_\_\_\_

Project Name: \_\_\_\_\_



SERIES SHAPE WATTAGE CCT (kelvin) FRAME LENS OPTIONS VOLTAGE FINISH

**SL - RND - 20LED - - OF - OPL - - UNV -**

## MODEL NUMBER DETAIL

SERIES	<input type="checkbox"/> <b>SL</b>	Solitaire Decorative LED Surface Mount Wall Pack
SHAPE	<input type="checkbox"/> <b>RND</b>	Round Bulkhead
WATTAGE	<input type="checkbox"/> <b>20LED</b>	19.7 (system) watt LED Module
COLOR (K)	<input type="checkbox"/> <b>30K</b> <input type="checkbox"/> <b>40K</b> <input type="checkbox"/> <b>50K</b>	3000K 4000K 5000K
FRAME	<input type="checkbox"/> <b>OF</b>	Open Face
LENS	<input type="checkbox"/> <b>OPL</b>	Opal Polycarbonate Lens
OPTIONS	<input type="checkbox"/> <b>DF</b> <input type="checkbox"/> <b>EM</b> <input type="checkbox"/> <b>SF</b> <input type="checkbox"/> <b>DF</b> <input type="checkbox"/> <b>P1</b> <input type="checkbox"/> <b>P2</b> <input type="checkbox"/> <b>SP</b>	Microwave Sensor w/dimming (for mounting heights of 15' or lower) Emergency Battery Backup (90 minutes) Single Fuse Double Fuse Photocell (120v) Photocell (277v) Surge Protector
VOLTAGE	<input type="checkbox"/> <b>UNV</b>	Universal Voltage (120v-277v) (50/60Hz); electronic dimmable driver
FINISH	<input type="checkbox"/> <b>BRZ</b> <input type="checkbox"/> <b>WHT</b> <input type="checkbox"/> <b>CC</b>	Bronze White Custom Color - Consult Factory



IP 67



*content of specification sheet is subject to change.*

N60 W14592 Kaul Avenue  
Menomonee Falls, WI 53051

P 877 965 0005  
[intrigueled.com](http://intrigueled.com)