



T1083LEDS-PA

16" SLIM LED HIGHBAY PRISMATIC ACRILIC REFLECTOR

JOB INFORMATION

Type: _____
 Catalog No: _____
 Project Name: _____
 Comments: _____
 Prepared by: _____

T1083LED

FEATURES

USE OF PRODUCT

The intended use of this product is for interior warehouses, gymnasium lighting, food service areas, or any commercial or industrial application.

HOUSING

Rugged die cast aluminum housing with electrical box and malleable hook.

OPTICS

Polished Aluminum Reflector.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 2700K, 3000K, 3500K, 4000K, or 5000K (standard) with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz. Driver provides dual dimming: Triac (forward-phase or leading-edge)/ELV (reverse-phase or trailing-edge) and 0-10V Dimming

Constant Current. Driver protections includes:

Output open load, over-current and short-circuit, and over-temperature with auto recovery. -30°C Min Temp. 40°C Max Temp.

MOUNTING

Standard hook mount. May be conduit mounted if remove hook. (3/4" IPS)

LISTINGS/COMPLIANCE

- CSA listed



ORDERING INFO

SERIES	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	REFLECTOR	DIAMETER	OPTIONS
T1083LEDS	30 - 30W/3042lm	UNV - 120V-277V	27K - 2700K	PA - Prismatic Acrylic	16 - 16"	BFL - Bottom flat lens
	45 - 45W/4692lm	347 ¹ - 347	30K - 3000K			SSC - Steel safety cable
	57 - 57W/6110lm	480 ¹ - 480V	35K - 3500K			EM - Emergency battery (Integral)
	80 - 80W/8012lm		40K - 4000K			MS - Motion sensor
	118 - 118W/11128lm		50K ² - 5000K			SDT - Step down transformer
						CPP110 - Cord plug polarized
						CPTL120 - Cord plug twist-lock(120V)
						CPTL277 - Cord plug twist-lock(277V)
						WG - Wire Guard

Notes

1. Step down transformer required
2. Standard color temperature

T1083LEDS-PA

16" SLIM LED HIGHBAY PRISMATIC ACRILIC REFLECTOR

DIMENSIONS

