

T1085LEDB-AL 19" LED HIGHBAY

FEATURES

USE OF PRODUCT

The intended use of this product is for interior warehouses, gymnasiums, food service areas, grocery stores, or any commercial or industrial applications.

CONSTRUCTION

Die-cast aluminum fixture with sealed lens for wet location applications.

FINISH

Bronze matt-finish, architectural powder coat over a precise chromate conversion coating. Consult factory for made to order architectural finishes

OPTICS

Available in clear prismatic acrylic or polished aluminum reflector.

ELECTRICAL

≥0.9 Power Factor <20% Total Harmonic Distortion 120-277v, Optional 347/480V; 50/60hz -40°C Min. Temperature +55°C Max. Temperature CRI: 72

LED

Available in 4000K and 5000K with CRI > 70. Optional photocell or motion sensor (consult factory for setting capabilities) available upon request for further energy savings and security measures.

MOUNTING

Standard hook mount. May be conduit mounted if remove hook (pendant may be provided by Rayon or others).

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz. Driver provides dual dimming: Triac (forwardphase or leading-edge)/ELV (reverse-phase or trailing-edge) and 0-10V Dimming Constant Current. Driver protections includes: Output open load, overcurrent and short-circuit, and over-temperature with auto recovery

WARRANTY

5 Year limited warranty

LISTING

UL-wet location DLC

ORDERING INFO

SERIES	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	HOUSING FINISH	REFLECTOR	MOUNTING	OPTIONS
T1085LEDB	135 - 135W/19400lm 175 - 175W/25600lm	UNV¹ - 120V-277V 347 - 347	40K - 4000K 50K¹ - 5000K	BZ - Bronze	AL - Aluminum	H¹ - Hook SM² - Stem Mount	EM - Emergency battery MS - Motion sensor
	200 - 200W/29800lm	480 - 480V					WG - Wire Guard

Notes 1. Standard 2. Consult factory for Stem mount lengths




JOB INFORMATION

Type: Catalog No: Project Name: Comments Prepared by:

RAYON LIGHTING GROUP, INC. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE. 1517 N. ALAMEDA ST. COMPTON CA 90222 | TEL 323.446.2626 | FAX 323.446.2606 | WWW.RAYONLIGHTING.COM

T1085LEDB-AL

DIMENSIONS





Hook

MOUNTING OPTION



Stem Mount

OPTIONAL EM



Emergency battery pack would provide the necessary brightness in emergency situations.

