



T617LED-O

LED OPEN SQUARE WALL PACK

JOB INFORMATION

Type: _____
Catalog No: _____
Project Name: _____
Comments: _____
Prepared by: _____

T617LED-O

FEATURES

USE OF PRODUCT

The intended use of this product is for decorative wall mount, building accents, pedestrian walkways, public access areas, or to accent landscape areas.

HOUSING

Die Cast gasketed aluminum housing with integral heat sinking and driver compartment. Nickel-Plated Stainless Steel Hardware.

FINISH

Matt-finished, architectural bronze powdercoat over a precise chromate conversion coating. Available in standard dark polyester bronze or consult factory for made to order architectural finishes.

OPTICS

Polycarbonate Opal Lens is sealed by a one-piece silicon gasket which prohibits entrance of outside contamination. Type IV distribution.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 4000K, or 5000K (standard) with CRI>80.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -40°C Min Temp. 50°C Max Temp.

MOUNTING

Surface mount.

LISTINGS/COMPLIANCE

- CEC Compliant emergency driver
- CSA -Suitable for wet location.
- ANSI/UL 1598
- 8750 IP65 Sealed LED compartment.



ORDERING INFO

SERIES	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	FINISH	OPTIONS
T617LED-O	12 - 12W/1676lm	UNV - 120V-277V	40 - 4000K	BZ ¹ - Bronze	PC - Photocell 120-277V
	17 - 17W/2263lm		50 - 5000K	MTO ² - Made to order	EM - Emergency battery
	25 - 25W/3520lm			MGTO ² - Marin grade made to order	SP10 - Surge protection 10KV
					S2 - Microwave Sensor w/Dimming

Notes
1. Standard finish.
2. RAL number required.

T617LED-O

LED OPEN SQUARE WALL PACK

DIMENSIONS

