

## **Approval Drawing**

Light Standard:F103-M-CP17-ST PAUL-6

Diffuser Type: White.

Diffuser Material: Acrylic

U.V. stabilized.

Optical System: Bare Lamp.

IES Type V.

Diffuser Holder Material: Made of cast aluminum and provided with four equally spaced 1/4"-20 UNC stainless steel allen head set screws with threaded insert.

**Ballast:** HPS high power factor mounted on removable plate. A quick disconnect wiring system allows for fast easy ballast maintenance.

Wattage - 70W Voltage -120V

Socket - Pulse Rated Mogul (4KV).

**Pole:**Cast aluminum tapered (5" to 4") shaft with 12 equaly spaced vertical flutes welded to base with a min. wall thickness of 3/8"

Base Cover: Cast Aluminum with door secured at the bottom by hooks cast onto the door and secured and the top by 1/4-20UNC stainless steel allen head screw.

Anchor bolts: 3/4"(19mm) x 24" (610mm) long with (2) nuts +(2) washers each installed on a 12" bolt circle. Anchor bolts and metal template are supplied by HCI.

**Finish:** Electrostatically applied thermoset polyester powder-coat finish with XL4 four part corrosion inhibiting process.

Color: Architectural Brown

(Sample to be approved by Architect)

Date: Nov.6, 2002 Drawing No: 4269

Model: F103-M-R4-WAC-70HPS-120V-BLCP17-ST PAUL-6-Architectural Brown

Project: Shepard Rd CSAH 17

Please Note: Fabrication will not begin until this drawing is approved, signed and returned to HCI



1280 Fewster Drive, Mississauga, Ontario, Canada L4W 1A4
Tel: (905) 238-2648 Fax: (905) 238-9060
Toll Free Canada & USA
E: sales@hcilighting.com WEB: www.hcilighting.com