

PCB FLOODLIGHT BRACKETS			
CATALOG #	# OF FLOODLIGHTS	POLE SIZING	LUMINAIRE WEIGHT (PER ARM)
PCB3-1	1	5.00-9.00 DIA	50 LBS. MAX

(4) 5/8-11 UNC X 3.00" THREADED ROD
 (8) 5/8 SAE FLAT WASHER
 (8) 5/8 LOCK WASHER
 (8) 5/8-11 UNC HEX JAM NUT


Ø5.00-Ø9.00
 POLE SHAFT

2 IN SCHED 40 STEEL PIPE
 (Ø2.38 OD X Ø2.07 ID)
 ASTM A500 GR.B

Ø.50
 WIRE ACCESS

NOTE: LUMINAIRE WEIGHT PER ARM 50 LBS MAX.
FINISH: BRACKET SHALL BE POLYESTER POWDER COAT FINISH IN
 A STANDARD COLOR OR HOT DIPPED GALVANIZED FINISH PER
 ASTM A123 SPECIFICATIONS.

SOME GEOGRAPHICAL AREAS HAVE SPECIAL WIND CONDITIONS THAT CAN CREATE WIND INDUCED VIBRATIONS CAUSING A FATIGUE PROBLEM. NO METHOD HAS YET BEEN FOUND FOR PREDICTING DESTRUCTIVE LIGHTING POLE VIBRATION. THESE CONDITIONS ARE UNIQUE AND CANNOT BE GUARANTEED AGAINST, AND ARE THE RESPONSIBILITY OF A LOCAL SITE ENGINEER.



DRAWN: L. GRUNIS	3/3/2017
CHECKED	
REVISION:	DATE:
APPROVED:	
QUOTE:	
S.O.#	
REF:	SCALE: NONE

UNITED LIGHTING STANDARDS
 A DWH COMPANY

23171 Groesbeck Hwy.
 Warren, MI 48089
 P: (586) 774-5650 | F: (586) 774-5706
www.unitedlightingstandards.com

TITLE:	
CATALOG:	
DWG NO: PCB3-1	SIZE: C SHEET 1 OF 1