


COLOR CHANGING + TUNING (OUTDOOR)

RGBCT-SERIES | COLOR CHANGING | RUBBER COATED **LINEAR LED LIGHTING**

ixture Type:	
Project:	
•	
Location:	



PRODUCT FEATURES

- · Ability to mix Kelvin temperatures
- 90+ CRI
- Dimmable
- 50,000 hour life
- 5-year warranty
- · UL-listed for indoor and outdoor use
- 3M™ industrial adhesive backing
- For use with electronic power supplies


RGB COLOR SPECTRUM



SPECIFICATIONS

Model	RGBCT-WR-24V (Outdoor)
Input Voltage	24V DC / Constant Voltage
Beam Spread	120°
Max Run Length	Unlimited, power every 25ft
Production Intervals	3.938" (100mm)
End Cap Dimensions	0.625" (15.2mm) × 0.375" (9mm)
Tape Dimensions	0.563" (14.2mm) × 0.25" (6mm)
Average Watts	4 W/ft
Lumens	340 max. lm/ft
CRI	3000K = 90+
Diode	5050
Dimming Options	RF, WiFi, DMX
Temp Range	-40°F (-40°C) to 149°F (65°C)
Rating	IP67

KELVIN COLOR TEMPERATURE SCALE



Conforms to ANSI/UL Standard 2108 Certified to CAN/CSA Standard C22.2 No. 250.0







