

JOB NAME

CONTACT

ORDERING CODE

Delta10

High Bay



22"



20"



16"

DESCRIPTION

Delta10 is an economical, high performance highbay fixture producing up to 27,000 delivered lumens. Multiple beam spreads are offered using a precision cut solid glass optic. Optional reflector options allow for controlled performance and aesthetics. 2% dimming is standard. Excellent for Schools, Retail, Production, Warehouses, Atriums, Theatre, Auditoriums and Gymnasiums. Delta10 carries a 5-year FIXTURE WARRANTY.

HOUSING

Extruded aluminum housing available in nano black coating only. Aluminum reflector has matte chrome finish.

MOUNTING

- Eyebolt attachment included (Eye inner diameter 30mm).

ELECTRICAL/CONTROLS

- 120-277Vac input, 50/60Hz, 260W max
- SJTW 18AWG/3C power cord lead 4-1/2' length, prewired to driver
- SVT 18AWG/2C dimming cord lead 4-1/2' length, prewired to driver
- Protections: short circuit, over current, over voltage, over temperature
- Maximum ambient temp for DIM10 option is 33°C/91°F, 10V option is 40°C/104°F. Consult factory for higher ambient options

LISTINGS

- ETLus Listed to UL1598 (suitable for dry locations only)
- cETL Listed to CSA C22.2 #9.0
- Made in the USA - meets the requirements of the Buy American provision within the ARRA
- DLC (see page 2 for more information)

LED INFO

- Citizen CLU058-1825C4: SDCM = 3-step MacAdam Ellipse, Lumen Maintenance: $L_{70}> 50,000$ hrs

ORDERING CODE



LM-79

PART NUMBER	680PB	
LED	CIT	
DELIVERED LUMENS	120LM ¹	12,000 lm
	140LM ¹	14,000 lm
	160LM ¹	16,000 lm
	180LM ¹	18,000 lm
	200LM ¹	20,000 lm
	240LM ¹	24,000 lm
	270LM ²	27,000 lm
Standard Configuration: 4000K 80CRI M20. Consult factory for other lumen options.		
CCT	27K	2700K
	30K	3000K
	40K	4000K
	50K	5000K
CRI	80	80 CRI
SHADE	M20 ³	20" aluminum shade, 90° beam
	IR16	16" impact resistant polycarbonate shade, 60° beam
	IR22	22" impact resistant polycarbonate shade, 70° beam
DIMMING	10V ¹	0-10V dimming to 10%
	DIM10 ²	0-10V dimming to 2%
ACCESSORIES ⁵	74221CL	16" clear drop lens
	74221FR	16" frosted drop lens
	74222CL	22" clear drop lens
	74222FR	22" frosted drop lens
	74221-CLAMP	16" clamp band / spring
	74222-CLAMP	22" clamp band / spring

ORDERING CODE

Follow the steps to specify your fixture, example:

680PB - CIT - 270LM - 40K - 80 - M20 - DIM10

LED	POWER
DELIVERED LM	W
12,000	87
14,000	107
16,000	122
18,000	148
20,000	180
24,000	220
27,000	260

Power Factor ≥ 0.9

NOTES

1. Only available for 10V dimming option. Dims to 10%.
2. DIM10 dimming option only available for 270LM.
3. Drop lens accessory not available for M20 shade.
4. Must order Drop Lens + Clamp Band / Spring separately.

ACCESSORIES



74221CL

16" Clear Drop Lens



74221-CLAMP

16" Clamp Band / Spring

MOUNTING OPTIONS

