CORNERSTONE W LED

Architectural Outdoor 🖉





FEATURES

- Clear Tempered Glass Diffusers
- CSA Listed Wet Location
- Die-Cast Aluminum Housing w/ Textured Black Polyester Powder Coat Finish
- Emergency Battery Available
- LED Light Fixture
- Mounts Direct to Flat Surface w/ Two #8 Wall Anchors (Not Included)

PROJECT: TYPE:


COMMENTS:

PO#:

Surge Protector Available

LINE DRAWING

LINE DRAWING NOT TO SCALE







 TERONLIGHTING.COM

 33 DONALD DR, FAIRFIELD, OH 45014

 P: 513.858.6004

 F: 513.858.6003

 F: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 1

QTY:

CORNERSTONE W LED

Architectural Outdoor

SP 🖬 📼

PROJECT: TYPE:

QTY:

PO#: COMMENTS:

PRODUCT CODE	TRIM	SOURCE/WATTAGE	DIMMING
CRNW-DL - Cornerstone W Downlight or Uplight Only CRNW-UDL - Cornerstone W Uplight and Downlight	Not Applicable	L10.0 L18.0 L29.0 L42.0 (UDL Only)	ZE - 0-10V Dimming
ORDER INFO			
CRNW-DL	L Not Applicable	L29.0	ZE

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

VOLTAGE	FINISH	COLOR TEMP	OPTIONS
UNV - 120 - 277V ORDER INFO	AC - Antique Copper AS - Antique SilverTB - Textured Black (Standard)BT - Bronze Mist 	30К - 3000К Color Temp 35К - 3500К Color Temp 40К - 4000К Color Temp 50К - 5000К Color Temp	 EB - Integral EM Battery (Downlight) (L112.3 Only) F - Fused PCL - Photocell TP - Tamper Resistant SPD - Surge Protection Device DP - Deep Housing
UNV	AC	30K	EB

Actual production units may vary from the values reported here by up to +/-10%

PERFORMANCE (DELIVERED LUMENS NO TRIM)

WATTAGE	3000K	LUMENS/WATT	3500K	LUMENS/WATT	4000K	LUMENS/WATT	5000K	LUMENS/WATT
L10.0	1206	113	1206	113	1243	116	1243	116
L18.0	2248	115	2248	115	2317	118	2317	118
L29.0	3061	106	3061	106	3156	109	3156	109
L42.0	4905	112	4905	112	5057	116	5057	116

ELECTRICAL DATA

WATTAGE	120V	208V	240V	277V	347V	480V
L10.0	.08A	.05A	.04A	.04A	N/A	N/A
L18.0	.17A	.10A	.08A	.07A	N/A	N/A
L29.0	.24A	.14A	.12A	.11A	N/A	N/A
L42.0	.35A	.20A	.18A	.15A	N/A	N/A

REPLACEMENT PART	PART NO	NOTES
Black Glass Lens	3702824	
Clear Glass Lens	37028	Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or 2 liability to modify any products previously manufactured, and without notice.