

MODEL **AUBURN** 

> **TYPE LED**

**SERIES COLUMN** 



# **ORDERING INFORMATION**

| Model AUBURN  |
|---------------|
| Type LED      |
| Series COLUMN |

| FIXTURE        | SIZE  | SOURCE            | VOLTS             | LAMP /<br>TEMP           | COLOR                     | LENS                              | OPTIONS  |
|----------------|---|-------------------|-------------------|--------------------------|---------------------------|-----------------------------------|--|
|                |   |                   |                   |                          |                           |                                   |  |
| AUB-C<br>(LED) | 6 (square) = 6" sq. x<br>156"H                      | 10W<br>20W<br>30W | U = 120v-<br>277v | 3K = 3000K = 90lm/w      | DB =<br>Dark<br>Bronze    | CFA = Clear<br>Frosted<br>Acrylic | SP = Surge Protection D = 0-10V Dimming Driver |
|                | 8 (square) = 8" sq. x<br>156"H                      | 40W<br>50W<br>60W | 8 = 480v          | 35K = 3500K<br>= 100lm/w | BK = Black                | WFA = White<br>Frosted            | MGF = Marine Grade Finish                      |
|                | 6R (round) = 6" dia.<br>x 156"H                     | 70W<br>80W        |                   | 41K = 4100K<br>= 110m/w  | WH = White<br>SL = Silver | Acrylic                           | CLED = Color Changing LED                      |
|                | 8R (round) = 8" dia.<br>x 156"H                     |                   |                   | 5K = 5000K =<br>120lm/w  |                           |                                   |  |
|                |   |                   |                   | 120III/W                 | CC =<br>Custom            |                                   |  |
|                | CH = Custom<br>height up to 20',<br>consult factory |                   |                   |                          |                           |                                   |  |



# **SPECIFICATIONS**

## Housing

Housing available using extruded round or square tube with .080 aluminum roof cap with supports fabricated for maximum strength. ETL listed for wet locations. Also available as bollard.

#### **LED**

High efficiency, long-life surface mounted LED's mounted on MPCB aluminum boards. 100,000 hour lifespan based on IES LM-80 results and TM-21 calculations. 0-10V dimming driver for 120/277 volt, constant current, metal case, 5 year warranty.

#### Lens

Lens is fabricated from premium acrylic. Specify clear frosted or white frosted lens.

#### **Finish**

Thermoset polyester oven-baked powder coat, in Dark Bronze. Custom colors are available to your specification. Marine Grade Finish available upon request.

# **Rating and Warranty**

ETL Listed for US and Canada for wet locations. 5-year warranty

### **Dimensions**



| A*   | В   | C**   | D**   |
|------|-----|-------|-------|
| 156" | 48" | 6" or | 6" or |
|      |     | 8"    | 8"    |

\*Custom height available, 20' max

\*\*Specify round or square tube

#### Mounting Template 8" Square

