



MODEL CORONA

TYPE **LED**

SERIES ARCHITECTURAL

ZUMA LIGHTING LLC325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004 INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM



ORDERING INFORMATION

Model CORONA

Type LED

Series ARCHITECTURAL



FIXTURE	HOUSING STYLE	WATTAGE	VOLTS	LAMP / TEMP	OPTICS	MOUNT	COLOR	OPTIONS
COR (LED)	SP = Spun Top CT = Cast Top	20W 30W 40W 60W 80W 90W 120W 150W 180W 200W 240W	U = 120v-277v 8 = 480v	3K = 3000K 4K = 4000K 5K = 5000K	T3 = 180° pattern T5 = 360° pattern	A = B = G = F = (wall mount) B = G = F = G = F = F = F = F = F = F = F	DB = Dark Bronze BK = Black WH = White SL = Silver CC = Custom	M = Motion Sensor SF = Single Fuse DF = Double Fuse PC = Photocell D = Dimming S = Surge Protection



SPECIFICATIONS

Fixture

The fixture housing is fabricated from a combination of heavy duty cast and spun aluminum components


LED

EncapLED, an IP66-rated ETL and DLC listed LED module system, combines optics and heat sink into one configurable unit which give precise light distribution. Available in types II, III, IV & V. It allows us to do 10w., 30w. & 40w. increment adjustment on light output. The module achieves 110-120 lm/w efficacy with LUXEON LUMILEDS TX CHIPS. Beside maximizing heat dissipation surface, we also utilize convectionbased heat management which creates additional air flow around each chip. Unlike a big metal heat sink where the temperature for the chips in the middle is higher than the rest, the heat of each EncapLED chip gets dissipated evenly. A better heat dissipation design keeps the junction temperature low and ultimately prolongs the life of the LED chips. Our modules are available in any of our fixture designs, as well as in a simple retro-fit kit form for existing fixtures.


Finish

Thermoset polyester oven-baked powder coat, in Dark Bronze. Custom colors are available to your specification.

Housing Style



Dimensions



*Custom measurements available upon request, consult factory for more information.