




ZUMALIGHTING
QUALITY OUTDOOR SOLUTIONS



MODEL
MARIPOSA

TYPE
LED

SERIES
BOLLARDS

ZUMA LIGHTING LLC
325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004
INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM

ORDERING INFORMATION

Model MARIPOSA
Type LED
Series BOLLARDS



FIXTURE	SIZE	SOURCE	VOLTS	LAMP / TEMP	OPTICS	COLOR	OPTIONS
MAR-B	38 = 38"H	10W 15W 20W 30W 40W	U = 120v- 277v 8 = 480v	2K = 2000K 3K = 3000K 4K = 4000K	T3 T5	DB = Dark Bronze BK = Black WH = White SL = Silver CC = Custom	SP = Surge Protection D= Dimming

SPECIFICATIONS

Housing

The fixture shaft is fabricated from heavy duty extruded aluminum. The Top is fabricated from heavy duty spun aluminum.

LED

EncapLED, an IP66-rated ETL and DLC listed LED module system, combines optics and heat sink into one configurable unit which give precise light distribution. Available in types II, III, IV & V. It allows us to do 10w., 30w. & 40w. increment adjustment on light output. The module achieves 110-120 lm/w efficacy with LUXEON LUMILEDS TX CHIPS. Beside maximizing heat dissipation surface, we also utilize convection-based heat management which creates additional air flow around each chip. Unlike a big metal heat sink where the temperature for the chips in the middle is higher than the rest, the heat of each EncapLED chip gets dissipated evenly. A better heat dissipation design keeps the junction temperature low and ultimately prolongs the life of the LED chips. Our modules are available in any of our fixture designs, as well as in a simple retrofit kit form for existing fixtures.

Mounting

Cast aluminum base plate secures to the housing. Mounting kit with anchor bolts, included.

Finish

Thermoset polyester oven-baked powder coat, in any standard color. Custom colors are available to your specification.

Certificates & Warranty

- ETL
- Suitable for Wet Locations
- 5-Year Warranty

Dimensions

