

MODEL SAN REMO

TYPE **LED** 

SERIES HISTORICAL




# **ORDERING INFORMATION**

**Model SAN REMO** 

**Type** LED

**Series** HISTORICAL



FIXTURE	WATTAGE	VOLTS	COLOR TEMP	OPTICS	MOUNT	COLOR	OPTIONS
SNR	20W 30W 40W 60W 80W 90W 120W 150W 160W	VOLTS  U = 120v- 277v  8 = 480v	27K = 2700K 3K = 3000K 4K = 4000K 5K = 5000K	T2 T3 T4 T5	DE DA BRO  C = WH  E = WH	DB = Dark Bronze  BK = Black WH = White  SL = Silver	M = Motion Sensor PC = Photocell D = Dimming S = Surge Protection
					G = ⊢ (wall mount)  I = post top / spider mount	CC = Custom	CL = Convex Lens 4S = Four Vertical Arms 2S = 2 Vertical Arms



## **SPECIFICATIONS**

## Housing

The fixture housing is fabricated from ultrathick, heavy duty cast aluminum. The housing comes standard with 3 decorative arms spaced 240° apart. Additional options include a fourth decorative arm spaced 90° apart, or 2 decorative arms spaced 180° apart.

## **Electrical Components**

EncapLED, an IP66-rated LED module system, combines optics and heat sink into one configurable unit which give precise light distribution. Available in types II, III, IV & V. It allows us to do 10w., 30w. & 40w. increment adjustment on light output. The module achieves 110-120 lm/w efficacy with LUXEON LUMILEDS TX CHIPS. Beside maximizing heat dissipation surface, we also utilize convectionbased heat management which creates additional air flow around each chip. Unlike a big metal heat sink where the temperature for the chips in the middle is higher than the rest, the heat of each EncapLED chip gets dissipated evenly. A better heat dissipation design keeps the junction temperature low and ultimately prolongs the life of the LED chips. Our modules are available in any of our fixture designs, as well as in a simple retro-fit kit form for existing fixtures.

#### **Finish**

Thermoset polyester oven-baked powder coat, in any standard color. Custom colors are available to your specification.

## Mounting

Fixture can be installed on arms or post-top.

### **Certificates & Warranty**

- DLC
- Suitable for Wet Locations
- 5-Year Warranty

### **Dimensions**

