



MODEL TACOMA

TYPE **LED**

SERIES COLUMN



ORDERING INFORMATION

N	Λ	Λ	d	ام	П	ГΑ	\mathbf{C}	\cap	٨/	ΙΔ
ш	78	v	u	C			\mathbf{C}	U	IV	ι∕¬

Type LED

Series COLUMN



FIXTURE	SIZE	SOURCE	VOLTS	LAMP / TEMP	COLOR	LENS	OPTIONS
TAC-C (LED)	10 = 8" sq. x 156" CH = Custom height, consult factory	10W 20W 30W 36W 40W 50W 60W 70W 80W 90W	U = 120v- 277v 8 = 480v	3K = 3000K = 90lm/w 35K = 3500K = 100lm/w 41K = 4100K = 110m/w 5K = 5000K = 120lm/w	DB = Dark Bronze BK = Black WH = White SL = Silver CC = Custom	CFA = Clear Frosted Acrylic WFA = White Frosted Acrylic	SP = Surge Protection D = 0-10V Dimming Driver MGF = Marine Grade Finish



SPECIFICATIONS

Housing

All parts are aluminum extruded square tube with 4 vertical aluminum square bar accents laser cut and milled for maximum strength. ETL listed for wet locations.

LED

High efficiency, long-life surface mounted LED's mounted on MPCB aluminum boards. 100,000 hour lifespan based on IES LM-80 results and TM-21 calculations. 0-10V dimming driver for 120/277 volt, constant current, metal case, 5 year warranty.

Lens

Lens is fabricated from premium acrylic. Specify clear frosted or white frosted lens.


Finish

Thermoset polyester oven-baked powder coat, in standard colors. Custom colors are available to your specification.

Certificates & Warranty

- DLC Listed
- ETL Verified
- Suitable for Wet Locations
- 5-Year Warranty

Dimensions



Α	В	С		
156"	96"	8" sq.		

*Custom height available

Mounting Template 8" Square

