

An Ameron[™] spun-cast concrete pole provides a uniquely premium appearance. Complete your package with a flag pole to match your lighting poles and bollards.

Reduce flag entanglement and prevent unauthorized removal with our internal halyard system utilizing a 360° rotating truck, marine quality halyard and hardware, and sleek-looking locking hand hole cover. For flag illumination, we can install optional inserts at 15' above grade to allow placement of light fixtures above vandals' normal reach. With the added protection of our anti-graffiti coating, vandal spray paint cleanup is quick and easy.

Nothing beats the beauty of spun-cast concrete. Our poles last a lifetime. Made in the U.S.A. 10 year warranty.

Materials and construction

Flag pole shafts are prestressed with high tensile steel cables, providing internal strength and resilience. High-strength concrete is then spun-cast to produce a pole of superior durability. Choose from our complete matrix of standard and pre-formulated colors, aggregates and finishes.

Applications

- Government and municipal properties
- Business buildings and commercial parks
- Malls, theaters and shopping areas
- Parks and community centers
- School, college and university campuses
- Memorial gardens
- $\bullet\,$ Stadiums and sporting areas
- Landmarks

Shapes and sizes

- · Available in 3 shapes: round, octagonal, square
- Heights 20'-50' above grade





Spun-Cast Concrete Flag Poles

Round					Embedded Style (FER)			Base Plate Style (FBR)			
Pole Height (nom.)	Top Diameter	Base Diameter	Ball Diameter	Flag Size	Catalog Number	Embedded Depth	Pole Weight	Catalog Number	Anchor Bolts	Bolt Circle	Pole Weight (lbs)
20'	5"	8"	6"	3' x 5'	FER-6	4'-11"	750	FBR-6	1" x 36"	11.5"	600
25'	5"	8.5"	6"	4' x 6'	FER-7.5	4'-11"	950	FBR-7.5	1" x 36"	11.5"	750
30'	5"	9.25"	6"	4' x 6'	FERX-9	5'-3"	1200	FBRX-9	1" x 36"	11.5"	920
35'	5"	12"	8"	4' x 6'	FERX-11	6'-8"	2100	FBRX-10.6	1" x 36"	14"	1200
40'	5"	12.5"	8"	5' x 8'	FERX-12	6'-7"	2500	FBRX-12	1" x 36"	15"	1800
45'	5"	13.5"	8"	5' x 8'	FERX-13.9	6'-11"	3000	FBRX-14	1" x 36"	16.5"	2350
49'	5"	13"	8"	5' x 8'	N/A	N/A	N/A	FBRX-15	1" x 36"	17.5"	2700
Square					Embedded Style (FEQ)			Base Plate Style (FBQ)			
Pole Height (nom.)	Top Diameter	Base Diameter	Ball Diameter	Flag Size	Catalog Number	Embedded Depth	Pole Weight	Catalog Number	Anchor Bolts	Bolt Circle	Pole Weight (lbs)
20'	5"	8"	6"	3' x 5'	FEQ-6	4'-11"	1150	N/A	N/A	N/A	N/A
25'	5"	8.5"	6"	3' x 5'	FEQ-7.5	4'-11"	1350	FBQ-7.5	1" x 36"	13"	1120
30'	5"	9"	6"	4' x 6'	FEQX-9.4	5'-3"	1775	FBQX-9	1" x 36"	15"	1450
35'	5"	10"	8"	4' x 6'	FEQX-10.6	5'-3"	2050	FBQX-11	1" x 36"	15.5"	1880
40'	5"	10"	8"	4' x 6'	FEQX-12.2	9'-3"	2760	FBQX-12.2	1" x 36"	16.5"	2150
Octagonal				Embedded Style (FEO)			Base Plate Style (FBO)				
Pole Height (nom.)	Top Diameter	Base Diameter	Ball Diameter	Flag Size	Catalog Number	Embedded Depth	Pole Weight	Catalog Number	Anchor Bolts	Bolt Circle	Pole Weight (lbs)
20'	5"	7.5"	6"	3' x 5'	FEO-6	4'-3"	750	FBO-6	1" x 36"	11.5"	600
25'	5"	8.5"	6"	3' x 5'	FEO-7.5	4'-11"	980	FBO-7.5	1" x 36"	11.5"	790
30'	5"	9.25"	6"	4' x 6'	FEOX-9	5'-3"	1300	FBOX-9	1" x 36"	11.5"	1000
35'	5"	10"	8"	4' x 6'	FEOX-10.6	5'-11"	1600	FBOX-10.6	1" x 36"	14"	1375
38'	5"	10"	8"	4' x 6'	N/A	N/A	N/A	FBOX-11.7	1" x 36"	14"	1600

Each flagpole includes:
6" or 8" gold ball, 1/4" internal halyard, easy-reach locking hand hole cover, integrated internal cleat, flag support chain and tensioning weight, (2) snaps for one flag

Optional accessories:Color-coordinated base cover, gold eagle

These poles reflect nominal pole heights. Contact Engineering to develop your own custom flagpole drawing.

