

PROJECT NAME:	APPROVED BY:	
CATALOG NO:	TYPE NO:	

SLIMLINE - SL Series

Self-Luminous Exit Signs

Sleek and Slender

The Slimline SL provides a quality architectural appearance in a low profile and durable aluminum housing. The SL requires no electricity, is completely energy efficient, is recyclable at the end of its useful life, and provides an ideal solution for green buildings.



Construction

- 100% reliable, maintenance free and always on
- Operating temperature range -55°C to 80°C
- 6" high letters with 3/4" stroke with Red, Green or Black background available
- Hidden tamper resistant wall mounting hardware
- Aluminum stencil face with field selectable chevron directional indicators
- Optional end or ceiling mount brackets are available
- Corrosion resistant extruded aluminum .05" minimum wall thickness fold-formed to prevent tampering
- Sustainable design and fully recyclable at the end of its useful life
- Standard finish is anodized aluminum. Also available in satin white or black enamel
- Polycarbonate shield seals lamp compartment and prismatic refractor lens
- Available in service life ratings of 10, or 20 years

Electrical

- Non-electrical, internally illuminated by sealed tritium gas light sources
- Requires no external light source, electrical power, wiring or batteries

Illumination

- 100 foot visibility rating
- Green light output for maximum visibility in emergency conditions

Certification

- As there is no electrical ignition source, the Slimline is suitable for use in hazardous atmospheres and damp locations. Meets NEC Article 500, Class 1, 11 and 111 conditions
- Suitable for use in Class 1, Div. 1, Groups C & D
- Tested, approved and listed by Underwriters Laboratories to UL 924 Standard, meets the requirements of NFPA 101 Life Safety Code



Warranty

- Limited warranty for the rated life of the product

ORDERING GUIDE - SL

Example: SL-10-2-G-W-PA

Model	Service Life	No. of Faces	Face Color	Frame Color	Options
SL Slimline Aluminum	10 10 Years 20 20 Years	1 Single Face 2 Double Face	R Red G Green B Black	BA Brushed Aluminum B Black W White	MB Mounting Bracket for Top or End Mounting PA 12" Swivel Pendant PB 24" Swivel Pendant PC 36" Swivel Pendant PD 48" Swivel Pendant <i>Note: For vandal resistant signs see data sheets SLV, INH or LEX</i>
SL					

Fill in fields from categories above and complete type and part number.

Type Number:

Full Part Number:

Slimline Self-Luminous Exit Signs SL Series

