

LUME-01-DW-HE Q-CAP Flexible Fixtures



Accentuate architectural details with three-sided illumination to create flexible and eye-catching lines of light.


- Fully encapsulated flexible fixture that is illuminated on 3 sides
- Perfect for interior and exterior applications
- Offered in two different outputs: Standard Output (3.0 W/ft) and High Output (5.0 W/ft)
- Unique up/down bend with a 6" bending radius provides creative freedom to create eye-catching lines of light
- 150° beam angle creates 3-sided illumination with ties to a retro aesthetic
- Compatible with different mounting hardware options to ensure product fits any design need
- Utilize translucent endcaps for continuous runs with no light loss

Output [Calculated L70 = 40000 hours]

Tested for LUME-01-DW-HE-WSC-DRY

CCT	SO Standard Output 1.5 W/ft Per Channel		HO High Output 2.5 W/ft Per Channel	
	ENC/TL		ENC/TL	
	LM/FT	CRI	LM/FT	CRI
2400K	90	93	121	92
2700K	64	97	133	97
3000K	**	**	**	**
4000K	**	**	**	**

Dimensions



Profile (Standard)

Wiring Detail



2" increments from 2"-191"

Part Number Builder

Product	Mounting	Rated	CCT	Output	Lens	Type	Connector/ Wire in	Connector/ Wire out	End Caps (No feed)	Length (in)
LUME-01-DW-HE					ENC/TL					
Voltage: 24 VDC Wattage: see table	WSC MC PPS-LP-CL-2 PPS-LP-CL-96 PPS-LP-CL-FT	DRY (IP20) WET (IP67)	24/30 27/40	SO (3.0W) HO (5.0W)	ENC/TL	S1 P1	BW CON6 CON24	N/A BW CON6 CON24	TL N/A	Max run: 191"

ENCAPSULATED PRODUCTS ARE NOT FIELD CUTTABLE

Single (Closed exit)
Pass through

1 BW comes in standard 24"- request custom length (Max 120") by writing it in inches next to "BW" in the order code box (ex. BW48)

2 Connector/Wire In or Out not needed to specify product. Standard configuration is type S1, Connector/Wire In: BW & Connector/Wire Out: N/A with white endcap (WH)

Flexibility








- Field modifications void Q-Tran warranty
- Up/Down Bend

- Data subject to change, all data has +/- 5% tolerance
- PPS-LP-CL-FT is to be cut at Q-Tran to requested length

LUME-01-DW-HE Q-CAP Flexible Fixtures




Mounting NOTE: 2 white snug clips provided per first 12", 1 for each additional 12". Other mounting styles incur additional charge, see price guide for details.

<p>WSC</p>  <p>White snug clip</p>	<p>MC</p>  <p>Magnetic clip (Cove use only)</p>	<p>PPS-LP-CL-2</p>  <p>Low profile PC mounting clip Clear finish</p>	<p>PPS-LP-CL-96</p>  <p>Low profile PC channel Clear finish</p>	<p>PPS-LP-CL-FT</p>  <p>Low profile PC channel Clear finish Custom length</p>
--	---	--	---	---

Type


SINGLE (Input only)

S1




PASS THROUGH (Input/Output)

P1



End Caps

TL



Translucent endcaps
.0" added at end

.00" dim spot


Bend Radius

Light source




Up/Down bend
6" bending
radius

Beam Angle




Connector/Wire – In/Out

BW




Bare Wire 24"

CON6



Connector 6"


CON24



Connector 24"

Lens with LED visibility

ENC/TL



Encapsulated
in translucent

Compatible Power Supplies

See website for additional power supply options

QTM-eLED+DMX



QTM-eLED+WD



QTM-eLED+AW



QTM-DRIVE



QOM-DRIVE

