

Fixture Type: _____

Model Number: _____

Project Name: _____



VETA

Amber LED Vaporproof (with Angled Shade)




Wall Mount
Vaporproof



Box Mount
Vaporproof



Pendant Mount
Vaporproof



Dimensions

| | |
|---------------------|---|
| Diameter (D) | 11¾" (296mm) |
| Height (A) | Pendant 16¼" (414mm) Box 15½" (394mm) Wall 19" (483mm) |

General: The Veta AmberLED vaporproof family with angled shades and shielded IES Type V distribution, are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications directly visible from the shore requiring monochromatic AMBER light. Veta vaporproof operates between 585nm-595nm, greater than 560nm required by the FWC. Applications include retail centers, hotels, parks, universities, office and commercial buildings, and medical facilities.

Housing: Heavy-duty die cast aluminum housing with integral heat sink; 3/4" NPS Threaded Mounts; includes shade required for FWC certification.

Finish: Smooth architectural silver powdercoat finish over a chromate conversion coating. For custom colors, please consult factory.

Lens: Flat clear tempered glass lens

Mounting: Wall Mount (-WM)
Pendant Mount (-PM)
Box Mount (-BM)

Wattage: Array: 23.0 watts System: 27.0 watts

Driver: Electronic Driver, 120-277V, 50/60Hz; Dimmable

Certifications: CSA listed for wet locations
ANSI/UL 1598, 8750
Operating temperature: -40°C to +50°C
IP66 Sealed LED Compartment
Florida Fish & Wildlife # 2018-001



certification # 2018-001



content of specification sheet is subject to change.

N60 W14592 Kaul Avenue
Menomonee Falls, WI 53051

P 877 965 0005
intrigueled.com

Fixture Type: _____
 Model Number: _____
 Project Name: _____



PHOTOMETRIC PERFORMANCE

Photometric Performance

| LED Board Watts | Drive Current (mA) | Input Watts | Optics |
|-----------------|--------------------|-------------|--------|
| AmberLED 23w | 116 | 27 | Type V |

Projected Lumen Maintenance

| Data shown for Amber LEDs | | | Compare to MH | | | |
|--------------------------------------|-------------|---------|---------------|------------|-------------|----------------------|
| TM-21-11 | Input Watts | Initial | 25,000 Hrs | 50,000 Hrs | 100,000 Hrs | Calculated L70@ 25°C |
| L70 Lumen Maintenance @ 25°C / 77°F | 27 | 1.00 | 0.96 | 0.92 | 0.84 | 187,000 |
| TM-21-11 | Input Watts | Initial | 25,000 Hrs | 50,000 Hrs | 100,000 Hrs | Calculated L70@ 50°C |
| L70 Lumen Maintenance @ 50°C / 122°F | 27 | 1.00 | 0.93 | 0.86 | 0.72 | 107,000 |
| TM-21-11 | Input Watts | Initial | 25,000 Hrs | 50,000 Hrs | 100,000 Hrs | Calculated L80@ 40°C |
| L80 Lumen Maintenance @ 40°C / 104°F | 27 | 1.00 | 0.94 | 0.88 | 0.76 | 82,000 |

NOTES:
 1. Projected per IESNA TM-21-11. Data references the extrapolated performance projections for the 116mA base model in a 25°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08.
 2. Compare to MH box indicates suggested Light Loss Factor (LLF) to be used when comparing to Metal Halide (MH) systems.

Accessories & Replacement Parts:



*Shown Mounted

| Accessories (Order separately, Field installed) | |
|--|---|
| VS30A | Angled Aluminum Shade, Repaintable Textured Gray Finish |
| VWGA | Wire Guard for Angled Shade, Stainless Steel |
| CPRB | Reducer Bushing, ¼" to ½", use with Swivel Mount |
| CPRB1 | Die Cast Round Electrical Box with Five (5) ½" Coin Plugs |
| CPRC1 | Backplate, ½" Coin Plugs |
| CPRB3 | Die Cast Round Electrical Box with Five (5) ¼" Coin Plugs |

| Mounting Accessories (Order separately, Field installed) | |
|---|---|
| CPSPR | Swivel Pendant Mount - Round, for Angled or Straight Ceilings, Fits ¼" Conduit, Includes Reducer Bushing (to ½") & Set Screw, Powdercoat Finish |
| CPSPS | Swivel Pendant Mount - Square, or Angled or Straight Ceilings, Fits ¼" Conduit, Includes Reducer Bushing (to ½") & Set Screw, Powdercoat Finish |



content of specification sheet is subject to change.

N60 W14592 Kaul Avenue
 Menomonee Falls, WI 53051

P 877 965 0005
 intrigueled.com

Fixture Type: _____
 Model Number: _____
 Project Name: _____



SERIES SHADE MOUNTING WATTAGE LED COLOR LENS OPTION VOLTAGE FINISH
VT - **ANG** - _____ - **23LED** - **AML** - **CGL** - _____ - **UNV** - _____

MODEL NUMBER DETAIL

- | | | |
|------------------|---|---|
| SERIES | <input type="checkbox"/> VT | Veta Amber LED Vaporproof |
| SHADE | <input type="checkbox"/> ANG | Angled Shade |
| MOUNTING | <input type="checkbox"/> BM Box Mount (Ceiling) <input type="checkbox"/> PM Pendant Mount <input type="checkbox"/> WM Wall Mount | |
| WATTAGE | <input type="checkbox"/> 23LED | 23-watt Amber LED Module |
| COLOR (K) | <input type="checkbox"/> AML | Amber (585nm-595nm) |
| LENS | <input type="checkbox"/> CGL | Flat Clear Tempered Glass Lens |
| OPTIONS | <input type="checkbox"/> DF Double Fuse <input type="checkbox"/> SF Single Fuse | |
| VOLTAGE | <input type="checkbox"/> UNV | Universal Voltage (120v-277v) (50/60Hz); electronic dimmable driver |
| FINISH | <input type="checkbox"/> SIL Silver <input type="checkbox"/> CC Custom Color - Consult Factory | |



content of specification sheet is subject to change.

N60 W14592 Kaul Avenue
 Menomonee Falls, WI 53051

P 877 965 0005
intrigueled.com

Jun-18