


## **5" CLC LED SERIES**

SURFACE Wall Mount Cornice Cove Light for Plaster or Drywall

LED cove light system is complete with reflector, LED, integral driver, and glass reinforced gypsum (GRG) housing.



## MUST BE ORDERED WITH CAST GRG HOUSINGS. COMES IN 96" LENGTH AND ARE FIELD CUTTABLE AND PAINTABLE

Model Number	Length of Light Component	Watts	Fixture Lumens for 35K
222W1CLC-E5	23"	22	2578
333W1CLC-E5	34-3/4"	33	3868
444W1CLC-E5	46-1/2"	44	5157

## **STANDARD FEATURES:**

Driver: 120/277 0-10 Volt OsramTrue 1% dimming c/CSA/us Damp Location Listed. IC Rated Made in the USA • U.S. Patent #7,824,059

## **AVAILABLE OPTIONS:**

DRIVER	ADD TO MODEL NUMBER
3-wire/Digital, Lutron ECO Systems L3D 1%	-DM6
2-wire, Lutron LTE 1% (120 Volt Only)	-DM7
Lower Lumen Output (All Driver Options) Must Consult Factory	-LL
Emergency Power Pack - REMOTE ONLY	-EPP
0-10 VOLT PROGRAMMABLE	ADD TO MODEL NUMBER
End of Life	-EOL
Soft Start	-SFT
Dim to Off	-DTO

LED (MUST SPECIFY)	ADD TO MODEL NUMBER
2700K (is standard 90+ CRI)	-27K
3000K	-30K
3500K	-35K
4000K	-40K
5000K	-50K

LENS	ADD TO MODEL NUMBER
Frosted Acrylic or Clear Acrylic	-FLF or FL