

Date:	
Project Name:	
SKU #:	

Contemporary Vanity Fixture 3CCT

Flush Mount



MOUNTING OPTIONS



Flush Mount
(Standard)

APPLICATIONS

Bathroom, Bedroom, Dressing Room, Etc

FEATURES

Construction

- Die-formed cold-rolled steel with powder coated paint.

Finish

- Brushed Nickel
- Black
- White

Electrical & Technical

- Input Voltage: 120 V
- Input Frequency: 60Hz
- Projected L70 > 50,000 hrs
- PF: >0.95
- CRI: 80 or 90 Option
- THD: <20%
- CCT Selectable: 3000K/4000K/5000K
- Operating Temp.: -4°F ~ 113°F
- IP Rating: Damp Location Rated

Optical

- High Transmission
- White Acrylic Lens
- 270° Beam Angle

Installation/Mounting

- Flush Mount:
 - 4" J-Box,
 - 4" Octagon J-Box,

Controls

- Triac Dimming

Dimmer Compatibility List:

Leviton: IPL06-10Z, 6672-11W, 6674-POW, DLS06-11Z
Lutron: TGCL-153P, MACL-153M, CTCL-153P, PD-6WCL

Lumen Output

- 1.5'/20W: 1,400lm
- 2'/25W: 1,725lm
- 3'/30W: 2,100lm
- 4'/35W: 2,450lm

Warranty

- 5 Year Warranty
See warranty documentation for more information.




ORDERING INFORMATION

EXAMPLE: VF3-2425-3CCT-BN

Series	Size/Wattage	CCT	Finish
VF3	1820 - 18"/20W 2425 - 24"/25W 3630 - 36"/30W 4835 - 48"/35W	3CCT - 3000K/4000K/5000K	BN - Brushed Nickel BK - Black WH - White

DIMENSIONS



LUMEN OUTPUT

SKU	Size (in)	Wattage (W)	Delivered Lumens (lm)	Efficacy (lm/W)
VF3-1820-3CCT-BN	18	20	1400	70
VF3-2425-3CCT-BN	24	25	1725	70
VF3-3630-3CCT-BN	36	30	2100	70
VF3-4835-3CCT-BN	48	35	2450	70