louis poulsen

KEGLEN WALL

Designed by Big Ideas



Description

The wall lamp's distinctive conical shade has a built-in curved diffuser. This ensures an attractive and glare-free light. A gentle light is also emitted upward through a discreet uniform opening in the top of the shade to create a perfect ambiance. The fixture can be mounted facing downward to direct the light to a specific spot, or upward for indirect light.

Variants	VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
	5743914364	WHT, T08	6.9 / 5.6 / 7.4 IN / 2.3 LB
	5743914377	BLK, T09	6.9 / 5.6 / 7.4 IN / 2.3 LB
	5743916207	BLK, T09	6.9 / 5.6 / 7.4 IN / 2.0 LB
	5743916252	WHT, T08	6.9 / 5.6 / 7.4 IN / 2.0 LB

Materials & Finishes

MATERIALS

Shade: Spun aluminum. Diffusor: Injection molded PC.

FINISHES

Black or white, matte, wet-painted.

louis poulsen

Mounting

Mounted directly to finished surface over a 4" octagonal junction-box. Switch: push button switch on the top wall box. Electronic LED driver is housed inside the wall box. For mounting instructions, see download section on the product detail page.

Information

Multi-function button switch: tap for switching on/off; press and hold for continuous dimming. May be disabled for on/off operation by remote wall light switch. An integrated memory function ensures that the lamp will return to its last dim level when turned on.

Head can rotate +/- 45° sideways.

Electrical:

System Wattage: 9W LED Wattage: 8W

Delivered lumens: 338 - 484 Efficacy: 40 lm/W - 57 lm/W (LED)

Certifications: cULus, Dry Location Protection class IP20

Controllability: Continuous dimming by integrated button switch.


Color Rendering: Ra≥90

Dim-to-warm LED CCT: 2700K at 100%; 2000K at max dim. For the E-socket product


variants, bulbs are not included. LED light source is part of the product.

Light distribution diagrams


CARTESIAN



ISOLUX



POLAR



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO. LIGHT SOURCE VOLTAGE/FRQ LUMEN FEATURES CABLE

louis poulsen

5743914364 LED 2700-2000K D2W 8.5W	457	-	With cord
5743914377 LED 2700-2000K D2W 8.5W	338	-	With cord
5743916207 LED 3000K 8.5W	358	-	With cord
5743916252 LED 3000K 8.5W	484	-	With cord