

## FLX38

LED Light Fixture, 3420-4140 Lumens, 38 Watts  
Track, Surface and Suspended

### Job Information

Project Name	
Type	
Location	
Quantity	
Date	

### Description

38W FLEX series is a high performance LED luminaire with powerful output of 4140 lumens, 90 CRI and smooth sharp cylindrical body with no visible heat sink. Lower energy consumption with crisp, precise CCT, beam control with excellent CRI for various lighting applications, from residential to retail lighting.

### Features

#### Body

Constructed of aluminum, the body features an aesthetically pleasing smooth cylindrical shape.

#### LED Characteristics

High powered 38W Luminus CXM-18 LED array maintains uniform intensity with a typical luminous flux up to 4140 lumens, with a typical CRI of 90.

#### Beam Spread

Fixture lens options available in 15°, 25°, 40° and 60° beam spread.

#### Mounting Options

Multiple mounting options for various applications. Available mounting options

include direct mounting onto a 4" octagonal junction box for flushmount and pendant applications, direct mounting onto a 3½" or 4" octagonal junction box for monopoint applications, and 1- or 2-circuit track connectors for track applications (compatible with A-Line, 2- and 3-circuit Powergear, H-style, L-style and Liteline tracks).

#### Operating Conditions

For indoor use only.

#### Quickship Made-To-Order

Made-To-Order products ship within seven business days of an order being released.


CCT	LUMENS
2700 K	3,420
3000 K	3,600
3500 K	3,960
4000 K	4,140



### SPECIFICATION

Approved Location	Dry / Indoor
Beam Angle	15° / 25° / 40° / 60°
CCT	2700 K / 3000 K / 3500 K / 4000 K
Certification	cETLus
Class II	Yes
Color	BK / SL / WH
CRI	90
Dimming	No
Input	100-135V AC, 60Hz
Lumens	Up to 4140
Lumens per Watt	Up to 109
Power Factor	0.95
Projected Life	70% @ 50,000 hrs
Warranty	5 years
Wattage	38W

### Technical Drawings



### Ordering Guide

#### Connector Type<sup>1</sup>



- FLX38 -

#### Color Temperature



#### Beam Angle



#### Mounting Type



#### Finish



QUICKSHIP  
7-DAY

Highlighted option denotes Quickship.

**BLANK** : No connector  
**A** : A-Line  
**H** : H-style  
**L** : L-style  
**LL** : Liteline  
**P2** : 2-Circuit Powergear  
**P3** : 3-Circuit Powergear

**27** : 2700 K  
**30** : 3000 K  
**35** : 3500 K  
**40** : 4000 K

**15** : 15°  
**25** : 25°  
**40** : 40°  
**60** : 60°

**F** : Flushmount  
**M** : Monopoint  
**P** : Pendant  
**T** : Track  
**TP** : Track Pendant

**BK** : Black  
**SL** : Silver  
**WH** : White

#### Notes:

<sup>1</sup> Available for Mounting Type "T" and "TP" only.

Quickship option is available on orders of 100 pieces or less, and will ship within 7 business days. Options must be selected from Quickship section to qualify.

Accessories are sold separately. For additional options please consult your Liteline representative.

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Liteline Corporation

Copyright © 2021

All rights reserved.

Telephone

416.996.1856

1.866.730.7704

Fax

905.709.5255

1.888.738.9736

LITELINE.COM

## Accessories



### FLX38-HC-xx

Honeycomb louver to reduce glare from light source. Available in Black (BK), Silver (SL) and White (WH).



### FLX38-SN-xx

Snoot to reduce glare and focuses projected light from light source. Available in Black (BK), Silver (SL) and White (WH).



### FLX38-EXT-xx<sup>1</sup>

4" Extender. Available in Black (BK), Silver (SL) and White (WH).



### FLX38-LINEAR-LENS

Linear spread lens.




### FLX38-SL-LENS

Soft lens.

#### Notes:

<sup>1</sup> Not recommended for use with Mounting Options "M" and "T".

## Ordering Guide (Complete with assembled accessories – must select at least one accessory)

Connector Type <sup>1</sup>	Color Temp.	Beam Angle	Fixture Type	Finish	Cylinder Extension <sup>2</sup>	Mounting Accessory	Optical Accessory	Lens
<b>FLX38</b>								
 <b>BLANK</b> : No connector <b>A</b> : A-Line <b>H</b> : H-style <b>L</b> : L-style <b>LL</b> : Liteline <b>P2</b> : 2-Circuit Powergear <b>P3</b> : 3-Circuit Powergear	<b>27</b> : 2700 K <b>30</b> : 3000 K <b>35</b> : 3500 K <b>40</b> : 4000 K	<b>15</b> : 15° <b>25</b> : 25° <b>40</b> : 40° <b>60</b> : 60°	<b>F</b> : Flushmount <b>M</b> : Monopoint <b>P</b> : Pendant, 55" <b>T</b> : Track <b>TP</b> : Track Pendant, 55"	<b>BK</b> : Black <b>SL</b> : Silver <b>WH</b> : White	<b>N</b> : No extender <b>X</b> : Cylindrical body extender, 4"	<b>ST</b> : No mounting accessory <b>R1</b> : 1' Rod <sup>3</sup> <b>R2</b> : 2' Rod <sup>3</sup> <b>R3</b> : 3' Rod <sup>3</sup> <b>R4</b> : 4' Rod <sup>3</sup> <b>C1</b> : 10' Cord <sup>3</sup> <b>C2</b> : 12' Cord <sup>3</sup> <b>C5</b> : 15' Cord <sup>3</sup>	<b>A</b> : No optical accessory <b>S</b> : Snoot	<b>F</b> : No lens <b>L</b> : Linear lens <b>T</b> : Soft lens <b>H</b> : Honeycomb louver

#### Notes:

<sup>1</sup> Available for Fixture Type "T" and "TP" only. <sup>2</sup> Only for Fixture Type "F", "TP" and "P". <sup>3</sup> Only for Fixture Type "TP" and "P".


Quickship option is available on orders of 100 pieces or less, and will ship within 7 business days. Options must be selected from Quickship section to qualify.

Accessories are sold separately. For additional options please consult your Liteline representative.


Due to our continued efforts to improve our products, product specifications are subject to change without notice.

## Technical Drawings (Assembled accessories)


With extender only




With snoot




With snoot + extender



With honeycomb louver




With honeycomb louver + extender




## Photometry

**FLX38-3040** : FLEX fixture, 38W, 3000 K, 40° beam spread.



### Beam Details



D	Lux	FC	L	W
4'	6761	628	2.6'	2.6'
8'	1690	157	5.1'	5.1'
12'	751	70	7.7'	7.7'
16'	423	39	10.2'	10.2'
20'	270	25	12.8'	12.8'

### Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	1696.0	39.48%
0-40	2534.0	58.99%
0-60	3527.0	82.10%
60-90	361.0	8.40%
70-100	259.0	6.03%
90-120	186.0	4.33%
0-90	3887.0	90.48%
90-180	300.0	6.98%
0-180	4296.0	100.00%