## **CORPUS** Outdoor

## 3-758-15



FIXTURE TYPE \_ LOCATION \_\_\_\_\_ DATE PROJECT\_



-15 Black

**LIGHT SOURCE** (1x) 8W LED with Driver on board, 3000K, CRI 90

LUMINAIRE POWER 9W at 120V 30000 hr RL **RATED LIFE** 

**OPTIONAL COLOR** 

**TEMPERATURES** 3000K Only

**LUMEN OUTPUT** Initial: 680 lm

Delivered: TBD Im (LM-79)

**INPUT VOLTAGE** 120V AC, 50/60Hz

**DIMMING** TRIAC Dimming 10-100%

CONSTRUCTION Cast Aluminum Housing

**DIFFUSER** - Matte White Glass

**FINISHES** Black (-15)


**MOUNTING** 4" Octagonal J-Box

(Installer must provide a bead of caulk between

fixture housing and mounting surface)

**STANDARDS** 

ETL Wet listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS** 

W: 4.875" H: 10.375" Ext: 5.875"

M.C: 2.9375" From top of fixture

Order example for standard fixture: 3-758-15 (x- Voltage - xxx-Sequence # - xx-Finish) 3: 120V Only



