



**LIGHT SOURCE**

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	LUMENS <small>*Avg. value, actual value dependent on bulb used</small>	CRI	VOLTAGE	DIMMING
<b>INCANDESCENT (MED E26)</b>					
<b>E26</b>	200W Max	1400*	100	120 VAC	Bulb Dependant

**SPECIFICATIONS**

**MOUNTING**

**SHADE & FINISHES**

BACKING PLATE  
6.25" Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum

COLBY SHADE  
Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum

MOUNTING ARM  
Hand Bent from 3/8" Diameter Aluminum Tubing

POWDER COAT FINISHES  
Polyester Powder Coat Finishes are Electro-Statically Applied and Thermocured

**CERTIFICATIONS, LISTINGS & WARRANTY**

**LIGHT SOURCE**

MADE IN THE USA  
Manufactured and hand-crafted in our 60,000 square foot facility located in Titusville, FL.

SOCKET  
E26 Medium Base Socket, 200W Max

CSA LISTED FOR WET LOCATIONS  
Includes Wall Sconce Without Optional Plug-In

CSA LISTED FOR DAMP LOCATIONS ONLY  
If Plug-In Option Selected, Includes Select Cords

LIMITED WARRANTY  
For additional information on our limited warranty, please see our Terms & Conditions.