



LIGHT SOURCE

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	LUMENS <small>*Avg. value, actual value dependent on bulb used</small>	CRI	VOLTAGE	DIMMING
INCANDESCENT (MED E26)					
E26	200W Max	1400*	100	120 VAC	Bulb Dependant

SPECIFICATIONS**MOUNTING**

BACKING PLATE
6.25" Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum

MOUNTING ARM
Hand Bent from 3/8" Diameter Aluminum Tubing

SHADE & FINISHES

COOPER SHADE
Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum

POWDER COAT FINISHES
Polyester Powder Coat Finishes are Electro-Statically Applied and Thermocured

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA
Manufactured and hand-crafted in our 60,000 square foot facility located in Titusville, FL.

CSA LISTED FOR WET LOCATIONS
Includes Wall Sconce Without Optional Plug-In

CSA LISTED FOR DAMP LOCATIONS ONLY
If Plug-In Option Selected, Includes Select Cords

LIMITED WARRANTY
For additional information on our limited warranty, please see our Terms & Conditions.

LIGHT SOURCE

SOCKET
E26 Medium Base Socket, 200W Max