




SPS-0650 REV A

LARAMIE NAUTICAL LED SERIES

JOB NAME: _____ FIXTURE TYPE: _____



BLE - _____ - _____ - _____ - _____ - _____ - _____ - _____ - _____ - _____

A B C D E F G

- LED16.8 -

H I J K

Order Example: BLE - C - LAR16 - 400 - CRZ - 400 - WC - 400 - NA - LED16 - 2700K - DL

A - MOUNTING STYLE

- C** Cord Hung
F Flush Mount
G Gooseneck
S Stem Mount

B - SHADE SIZE**LARAMIE:**

- LAR12** 12" Shade
LAR16 16" Shade

C - SHADE FINISH**POWDER COAT FINISHES¹:**

- | | |
|------------|-------------------|
| 100 | Black |
| 105 | Textured Black |
| 106 | Matte Black |
| 200 | White |
| 206 | Matte White |
| 300 | Dark Green |
| 307 | Emerald Green |
| 311 | Jadite |
| 370 | Mint |
| 380 | Chartreuse |
| 390 | Teal |
| 400 | Barn Red |
| 420 | Orange |
| 470 | Watermelon |
| 480 | Blush Pink |
| 490 | Magenta |
| 495 | Sherbet Orange |
| 500 | Buttery Yellow |
| 570 | Sunflower |
| 600 | Bronze |
| 601 | Chocolate |
| 605 | Rust |
| 615 | Oil-Rubbed Bronze |
| 700 | Royal Blue |
| 705 | Navy |
| 710 | Cobalt Blue |
| 715 | Delphite Blue |
| 790 | Lavender |
| 800 | Industrial Grey |
| 805 | Charcoal Granite |
| 810 | Graphite |
| 975 | Galvanized |

D - MOUNTINGPlease Note: If Flush Mount [F] is selected in **Section A**, please select **NA**

- NA** Not Applicable

CSA LISTED CORDS:

- SBK** Standard Black
SWH Standard White
CSB Black Cloth
CSW White Cloth
CMG Grey Cloth
CSR Red Cloth
CRZ Red Chevron Cloth
CSBB Black & Brown Cloth
CSRW Red & White Cloth
CSGW Gold & White Cloth
CSBG Black & Gold Cloth
CSBW Black & White Cloth
CSBP Black & Pink Cloth
CSUW Blue & White Cloth

GOOSENECK OPTIONS:

- | | | |
|-----------------------|------------|------------|
| G1 | G11 | G25 |
| G2 | G12 | G26 |
| G3² | G13 | G32 |
| G4² | G14 | G34 |
| G5 | G15 | G35 |
| G6 | G16 | G36 |
| G7 | G17 | G40 |
| G8 | G19 | G64 |
| G9 | G22 | G65 |
| G10 | G24 | |

STEM MOUNT OPTIONS:

- ST506** .5" Stem Mount, 6"
ST512 .5" Stem Mount, 12"
ST518 .5" Stem Mount, 18"
ST524 .5" Stem Mount, 24"
ST536 .5" Stem Mount, 36"
ST548 .5" Stem Mount, 48"
ST706 .75" Stem Mount, 6"
ST712 .75" Stem Mount, 12"
ST718 .75" Stem Mount, 18"
ST724 .75" Stem Mount, 24"
ST736 .75" Stem Mount, 36"
ST748 .75" Stem Mount, 48"

E - MOUNTING FINISHPlease Note: See **Section C** for Finish Options. 980-Brushed Aluminum is also available for Gooseneck (Not Available with G36, G40, G64 & G65) and Stem mounting styles.

(I) If Cord Hung [C], selection identifies canopy finish

(II) If Stem Mount [S] Mounting Style, selection identifies stem and canopy finish

(III) If Flush Mount [F] Mounting Style, selection identifies hex coupler and canopy finish.

- 980** Brushed Aluminum

F - SHADE ACCESSORY

- NA** None
TGG Heavy Duty Guard
CGG Cast Guard
WGG Wire Guard

G - SHADE ACCESSORY FINISHPlease Note: See **Section C** for Finish Options. If no accessory is selected in **Section F**, please select **NA**

- NA** Not Applicable

H - GLASS OPTIONS

- CLR** Clear Glass
FST Frosted Glass
RIB Ribbed Glass

I - MOUNTING ACCESSORY

Please Note: Mounting Accessories below are only applicable with select Mounting Styles. Please refer to product listings on our website for further detail

- NA** None/Not Applicable
HSC Hang Straight Canopy³
HDSMC Heavy Duty Stem Mount Canopy³
HDBP Heavy Duty Backing Plate^{4,5}
DD Dusk-to-Dawn Photocell^{4,5}
DBPC Decorative Backing Plate Cover^{4,5}
DCHX Decorative Backing Plate Cover & Hex Cover^{4,5}

J - LIGHT SOURCE

- LED16.8** 1600 Lumen


K - COLOR TEMPERATURE

- 2700K** 2700K, Warm White
3000K 3000K, Neutral White
3500K 3500K, Bright White
4000K 4000K, Cool White


IMPORTANT: (1) All Powder Coat finished shades, Galvanized excluded, feature a white interior (2) Not compatible with 16" shade size (3) Only applicable if Stem Mounting Style is selected in Section A (4) Only available if Gooseneck Mounting Style is selected in Section A (5) Not available with G3, G4, G11, G15, G19, G26 & G40 Gooseneck options

MOUNTING STYLE


CORD HUNG PENDANT (C)




FLUSH MOUNT (F)




STEM MOUNT PENDANT (S)



GOOSENECK (G)



LUMINAIRE DIMENSIONS



SHADE CODE	HEIGHT (A)	DIAMETER (B)	EXTENSION (C)
LAR8	5.7"	8"	N/A
LAR12	8"	12"	5"
LAR16	10"	16"	3"

SPECIFICATIONS

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA
 Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility
 Located in Titusville, FL

CSA LISTED FOR WET LOCATIONS
 Includes All Gooseneck, Stem and Flush Mounting Styles

CSA LISTED FOR DAMP LOCATIONS
 Includes All Cord Hung Mounting Styles

LIMITED WARRANTY
 For Additional Information on Our Limited Warranty, Please See
 Our Terms & Conditions

CONSTRUCTION & FINISH

POWDER COAT SHADE
 Hand-Spun from High Purity 3003-O Temper Aluminum

GALVANIZED SHADE
 Hand Spun from High Quality Galvanized Steel

POWDER COAT FINISHES
 Polyester Powder Coat Finishes Are Electro-Statically Applied and
 Thermocured

STEM
 1/2" Nominal (0.84" Actual) or 3/4" Nominal (1.05" Actual) Sch 40,
 6063 Aluminum Mounting Stem. Custom Lengths Available upon
 Request.

GOOSENECK
 1/2" Nominal (0.84" Actual) or 3/4" Nominal (1.05" Actual) Sch 40,
 6063 Aluminum Gooseneck

CORD
 Cord-Hung Pendants Include 7' of Standard Cord or 5' of Cloth
 Cord, +/- For Socket Orientation

LED16.8 LIGHT SOURCE

AVAILABLE CCT: 2700K, 3000K, 3500K, 4000K

90+ CRI

LED16.8 ELECTRICAL/LED DRIVER

DRIVE CURRENT: 400mA

POWER FACTOR > 0.9

EFFICIENCY: UP TO 85% TYPICAL

INPUT VOLTAGE: 120 VAC

CLASS 2 POWER SUPPLY

LED DRIVER LIFETIME: > 100,000 HOURS (@ 25 DEG C AMBIENT)

IP20 MINIMUM RATING CASE WITH SILICONE-BASED POTTING

PROTECTIONS

Output Open Load, Over-Current and Short-Circuit (hiccup), and
 Over-Temperature with Auto Recovery

CONDUCTED AND RADIATED EMI
 Compliant with FCC CFR Title 47 Part 15 Class B (120 VAC), Class A
 (277 VAC) and EN55015 (CISPR 15) at 220, 230 and 240 VAC

COMPLIANT WITH
 Complies with Energy Star® DLR (DesignLight Consortium®) and CA
 Title 24 Technical Requirements

DIMMING

LED 16.8
 Triac & ELV Dimming at 120VAC, Able to Dim down to 1%.
 Dependent on Specific Dimmer.
 0-10V Dimming Available upon Request.

COMPATIBLE DIMMERS
 Consult Factory for Additional Information on Dimming