

		FIXTU	JRE TYPE:			Ĺ
BLE - C -	- 10					
	Α	В	C	D	E	F
Order Examp	ble: BLE - C - DBW10 - 1004	- SBK - WC - 100 - 250 - E26				
A - SHAD	DE SIZE	C - SHADE ACCESSOR		SHADE ACCESSORY FIN	ISH E - CAN	IOPY FINISH
SBK SWH CSB	8" Shade ¹ 10" Shade 12" Shade S TED CORD OPTIONS: Standard Black Standard White Black Cloth	NA Not Applicab WC Wire Cage ACR Acrylic Diffus D - SHADE ACCESSOR Please Note: If no Shade Accessor in Section C, please select NA. 1 Finish is selected, accessory will I coat painted-to-match NA Not Applicable	er ^{2,3,4} POW 60 64 64 64 70 71 74 74 74 74	CONTINUED)OWDER COAT FINISHES:601Chocolate605Rust615Oil-Rubbed Bronze700Royal Blue705Navy710Cobalt Blue715Delphite Blue790Lavender800Industrial Grey805Charcoal Granite810Graphite975Galvanized	350 355 455 550 650 750 765 850	Black White Vintage Green Jadite Cherry Red Yellow Bronze Cobalt Blue Delphite Blue Graphite
CSW CMG CSR CRZ	White Cloth Grey Cloth Red Cloth Red Chevron Cloth	POWDER COAT FINIS 100 Black 105 Textured Bla	ck 81			F - SOCKET TYPE
CSBW CSRW CSBG CSBP CSGW CSUW CSBB	Black & White Cloth Red & White Cloth Black & Gold Cloth Black & Pink Cloth Gold & White Cloth Blue & White Cloth Black & Brown Cloth	106Matte Black200White206Matte White300Dark Green307Emerald Gre311Jadite370Mint380Chartreuse	en 31 31 32 31 32 44	CELAIN FINISHES: 50 Black 50 White 50 Vintage Green 55 Jadite 55 Cherry Red	E26 GU24	200 Watt Max 23 Watt Max ^{1,5}
NON-CSA OPTIONS TBK TWH TBR TRD TPT TBW TRW TBB	A LISTED CORD Black Cotton Twist White Cotton Twist Brown Cotton Twist Red Cotton Twist Putty Cotton Twist Black and White Twist Red and White Twist Brown and Beige Twist	390Teal400Barn Red420Orange470Watermelon480Blush Pink490Magenta495Sherbet Oran500Buttery Yellc570Sunflower600Bronze	65 75 76 81 95	 50 Yellow 50 Bronze 50 Cobalt Blue 55 Delphite Blue 50 Graphite 50 Metallic Chrome 		

IMPORTANT: (1) Not available with Acrylic Diffuser option (2) Not available with GU24 Socket Type (3) Acrylic Diffuser accessory reduces incandescent wattage to 60W (4) Fixture is UL Listed for Damp Locations with Acrylic Diffuser (5) Fixtures configured with GU24 socket are non-returnable

MOUNTING DIMENSIONS





BARN LIGHT ELECTRIC CO.

SPECIFICATIONS

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA

Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, Fl

CSA LISTED FOR DAMP LOCATIONS ACR is UL Listed for Damp Locations

LIMITED WARRANTY For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions

CONSTRUCTION & FINISH

SHADE & CANOPY Hand-Spun from 20 Gauge Porcelain Steel

PORCELAIN FINISHES Applied by Hand and Fired in a High Temperature Oven

POWDER COAT FINISHES Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured

CORD

Cord-hung Pendants Include 7' of Standard Cord or 5' Of Cotton Cord, +/- For Socket Orientation

LIGHT SOURCE

INCANDESCENT Medium Base E26 Socket, 120 VAC, 200 Watt Max

COMPACT FLUORESCENT Bi-Pin Base GU24 Socket, 120 VAC, 23 Watt Max